



Mobil Super™ TRC - PRO 20W-50

Mobil Passenger Vehicle Lube , Nicaragua

Product Description

Mobil Super™ TRC - Pro 20W-50 oils are conventional high-viscosity multigrade engine oils that provide extra protection to your engine, delivering 35% better wear protection than industry standards* giving your engine the proven protection and performance you expect under a wide variety of operating conditions for long engine life.

Mobil Super TRC - Pro 20W-50 oils contain TRC™ that is heat activated and help maintain the optimal viscosity, surpassing the protection expectations for high viscosity, high quality SN category approved gasoline engine oils.

Mobil Super TRC - Pro 20W-50 oils are backward compatible with earlier performance levels such as API SM, SL, and SJ and previous ILSAC categories.

Features and Benefits

35% better wear protection against industry standards*

Helps extend engine life

Excellent engine cleanliness

Engine protection under a wide variety of operating conditions

Helps reduce engine wear and deposits

Meets or exceeds the latest industry specification API SN

*Better wear protection compared to API SN engine test requirement in ASTM D6891 Seq. IVA test

Applications

Mobil Super TRC - Pro 20W-50 oils are recommended for current and earlier gasoline fueled passenger cars, sport utility vehicles, vans and light duty trucks where a higher viscosity API SN, SM, SL or SJ oil is preferred or recommended. They also meet ILSAC GF-5 (Starburst Certification Symbol).

Mobil Super TRC - Pro 20W-50 oils have a higher viscosity which provides engines with full protection under higher operating speeds, higher ambient temperatures, and other adverse conditions.

Before using a Mobil Super TRC - Pro 20W-50 motor oils, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API Service Classification.

Specifications and Approvals

This product meets or exceeds the requirements of:

API SL

API SM

API SN

Properties and Specifications

Property	
Grade	SAE 20W-50
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	19.0
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	154
Pour Point, °C, ASTM D97	-30
Flash Point, Cleveland Open Cup, °C, ASTM D92	230
Density @ 15 C, g/ml, ASTM D4052	0.880

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2023

ExxonMobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved