



Mobil Super™ 1000 20W-50

Mobil Passenger Vehicle Lube , Oman

Premium Multigrade Passenger Vehicle Engine Oils

Product Description

Mobil Super™ 1000 20W-50 is a premium quality mineral motor oils. The product is designed to provide protection for your engine under most operating conditions.

Features and Benefits

Mobil Super 1000 provides engine protection and helps promote long engine life.

- Extended protection against engine wear and deposits formation
- Engine protection during start up
- Helps combat sludge

Applications

Mobil Super 1000 20W-50 has been formulated to be suitable for use in vehicles requiring an API SL claim. ExxonMobil particularly recommend Mobil Super 1000 for daily driving under normal conditions:

- Passenger cars, SUV's, light trucks and vans (Gasoline engines) requiring an API SL
- Normal Operating Conditions
- Suitable for use under a wide range of temperature conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product meets or exceeds the requirements of:

API SL

API SM

API SN

API SN PLUS

API SP

Properties and Specifications

Property	

Property	
Grade	SAE 20W-50
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	146.9
Pour Point, °C, ASTM D97	-27
Flash Point, Cleveland Open Cup, °C, ASTM D92	239
Cold-Cranking Simulator, Apparent Viscosity @ -15 C, mPa.s, ASTM D5293	6300
Viscosity Index, ASTM D2270	128
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	17

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2023

ExxonMobil



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved