



Mobilube™ 1 SHC 75W-90
Mobil Commercial Vehicle Lube , Peru
Fully Synthetic Automotive Gear Lubricant

Product Description

Mobilube 1 SHC 75W-90 is a fully synthetic, high performance commercial gear lubricant formulated using advanced base oils and the latest technology additive s. This lubricant is engineered for heavy duty manual transmissions and rear axles where operations require gear lubricants with excellent load-carrying capability ove operating temperatures and where extreme pressures and shock loading are expected. Mobilube 1 SHC 75W-90 has excellent thermal and oxidation stabilit inherent Viscosity Index (VI), extremely low pour point, and outstanding low temperature fluidity.

The state-of-the-art technology behind Mobilube 1 SHC 75W-90 delivers outstanding viscosity-temperature properties necessary for wide temperature applications, optimised protection against thermal degradation and oxidation, wear and corrosion, shear stability, extended service capability, and potential fuel eci improvement. Mobilube 1 SHC 75W-90 incorporates the latest technology in synthetic basestocks and advanced additives providing significant advantage conventional gear oils. This technology also ensures effective lubrication since this product remains fluid without channeling at subzero temperatures. Mobilube 75W-90 meets or exceeds the requirements of the API Service MT-1/GL-4/GL-5 gear oil service classifications.

Features and Benefits

Today's technology has vastly improved the performance capabilities of heavy duty on and off highway equipment load, torque, speed, and control through innoc drivetrain designs. These designs have changed and increased the requirements of lubricants to deliver higher levels of performance, increased productivity, and re operating costs. For heavy-duty final drives, friction control, wear protection, thermal stability, shear stability, rust and corrosion prevention, and seal protecti features that must be optimally balanced to provide extended gear and seal life, smooth operation, improved fuel economy, and high load high torque capability wide range of applications. Mobilube 1 SHC 75W-90 is engineered to deliver exceptional performance and reduce total lube-related operating cost in modern duty drivetrains. The key benefits include:

Features	Advantages and Potential Benefits
Exceptional thermal stability and resistance to high temperature oxidation	Long gear and bearing life due to minimal deposits Long seal life
Outstanding protection against low speed/high torque wear, spalling, and against high speed scoring	Increased load-carrying capability. Reduced maintenance costs and long equipment life
Excellent shear stability	Retains viscosity and film strength under severe operating conditio prevent wear
Excellent rust, staining, and corrosion protection of copper and its alloys	Improved synchroniser performance and long component life
Enhanced frictional properties	Fuel economy potential and improved shiftability
Outstanding low temperature fluidity versus mineral oils	Reduced wear and ease of start up--even in arctic conditions
Wide multipurpose capability	One lubricant for heavy-duty manual transmissions and rear axles
Good resistance to foaming	Maintains film strength for effective lubrication
Compatible with typical automotive seals and gaskets	Minimum leakage and reduced contamination

Applications

- Recommended by ExxonMobil for use in:
- On-highway light- and heavy-duty trucks, busses, vans, and cars
 - Off-highway industries including: construction, quarrying, and agriculture

- Transmissions and axles and other applications where lubricants meeting API GL-4, GL-5 or MT-1 where mild extreme pressure gear lubricants are recommended
- Not intended for automatic, manual, or semi-automatic transmissions for which engine oil or automatic transmission fluids are recommended
- Applications where extended service intervals and warranties are required

Specifications and Approvals

MOBILUBE 1 SHC 75W-90 meets or exceeds the requirements of the following industry and builder specifications:

Scania STO 2:0 A FS

This product has the following approvals:

MAN 341 Typ Z2

MAN 342 Typ S1

MB-Approval 235.8

SAE J2360

ZF TE-ML 02B

ZF TE-ML 12L

ZF TE-ML 12N

ZF TE-ML 16F

ZF TE-ML 17B

ZF TE-ML 19C

Mack GO-J

ZF TE-ML 05A

ZF TE-ML 21A

This product is recommended for use in applications requiring:

API GL-4

MAN 341 Typ E3

ZF TE-ML 08

This product meets or exceeds the requirements of:

API GL-5

API MT-1

R. Bosch AS TE-ML 08

This product meets or exceeds the requirements of:
Scania STO 1:0
ZF TE-ML 07A
Scania STO 1:1 G

Properties and Specifications

Property	
Grade	SAE 75W-90
Density @ 15 C, kg/l, ASTM D4052	0.87
Flash Point, Cleveland Open Cup, °C, ASTM D92	202
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	15.1
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	102
Pour Point, °C, ASTM D97	-54
Viscosity Index, ASTM D2270	156

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024
Terpel Comercial del Perú S.R.L.
Av. Jorge Basadre Grohmann 347,
Interior 1005, San Isidro
Lima, Perú
24 Horas emergencia en salud LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect pro performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without nc All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intende override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTOMOBILE

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved