



Mobil Delvac™ 25W-50

Mobil Commercial Vehicle Lube , Peru

High Performance Diesel Engine Oil

Product Description

Mobil Delvac™ 25W-50 is a high viscosity, high performance diesel engine oil that provides proven protection for diesel engines operating in severe service applications. Mobil Delvac 25W-50 is recommended for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

Features and Benefits

The technology in Mobil Delvac 25W-50 delivers excellent performance in both naturally aspirated as well as turbo-charged diesel powered equipment. The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
TBN reserve	Deposit control and acid neutralization
High Viscosity and Stay-in-grade shear stability	Reduced oil consumption, increased wear protection and high oil pressure across a wide operating temperature range
Excellent detergency/dispersancy	Cleaner engines and prolonged engine life
Component compatibility	Long gasket and seal life

Applications

- Naturally aspirated and turbo-charged diesel powered equipment European, Japanese, and American manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture

Specifications and Approvals

This product is recommended for use in applications requiring:
API CD
API CF-4

Properties and Specifications

Property	
Grade	SAE 25W-50

Property	
Ash, Sulfated, mass%, ASTM D874	0.9
Density @ 15 C, kg/l, ASTM D4052	0.895
Flash Point, Cleveland Open Cup, °C, ASTM D92	237
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	20.5
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	213
Pour Point, °C, ASTM D97	-27
Total Base Number, mgKOH/g, ASTM D2896	8.4
Viscosity Index, ASTM D2270	113

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2020

Terpel Comercial del Perú S.R.L.

Av. Camino Real 456,

Torre Real Piso 14 San Isidro

Lima Perú

24 Horas emergencia en salud LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved