



MOBIL DELVAC MODERN 15W40 FULL PROTECTION MINE

Mobil Commercial Vehicle Lube , Peru

High Performance Diesel Engine Oil

Product Description

Mobil Delvac Modern 15W-40 Full Protection Mine is a diesel engine oil formulated to offer ring liner wear protection, viscosity control and bearing corrosion protection for the higher demands of high horsepower off-highway engines.

Features and Benefits

Mobil Delvac Modern 15W-40 Full Protection Mine is formulated with optimized base oil technology, to deliver extended performance oil drain intervals¹. This proprietary formulation delivers wear protection, outstanding oxidation stability, and exceptional TBN retention.

Mobil Delvac Modern 15W-40 Full Protection Mine also provides outstanding resistance to oil oxidation, corrosive and abrasive wear, and high temperature deposits.

¹ Results vary based on vehicle/engine condition, driving and environmental conditions. Consult OEM or ExxonMobil before implementing extended ODI, especially if the equipment/vehicle is under warranty.

Features	Advantages and Potential Benefits
Outstanding oxidation stability	Extended ODI potential ¹ .
Resistance to corrosive and abrasive wear	Long life of critical wear surfaces.
Excellent soot and viscosity control	Greater engine efficiency, long engine life and long oil life.
Excellent oil consumption control	Lower oil costs due to less make-up oil during operation
Outstanding TBN reserves	Corrosion protection and extended drain intervals for both new and old engines
Low temperature fluidity and pumpability	Formulated for smooth starting in cold weather
Component compatibility	Long gasket and seal life
Low ash formulation meeting API CK-4 and CJ-4 requirements	Long emissions aftertreatment life (DPF, DOC and SCR)

Applications

- Designed primarily for heavy duty diesel engines in mining applications.
- Recommended for the latest heavy duty diesel engines, including those equipped with aftertreatment systems and EGR.
- Recommended for diesel applications using older and naturally aspirated conventional designs.
- Off-highway applications including construction.

- Off-highway applications operating in severe low speed/heavy load conditions using up to 500 ppm sulfur fuels.

Specifications and Approvals

This product has the following approvals:
Cummins CES 20081
Cummins CES 20086

This product has the following builder approvals:
MTU Oil Category 2.1

This product meets or exceeds the requirements of:
API CI-4
API CI-4 PLUS
API CJ-4
API CK-4
Caterpillar ECF-3

Properties and Specifications

Property	
Grade	SAE 15W-40
Ash, Sulfated, mass%, ASTM D874	1
Density @ 15.6 C, g/ml, ASTM D1298	0.8734
Flash Point, Cleveland Open Cup, °C, ASTM D92	227
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	16.2
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	126
Pour Point, °C, ASTM D97	-24
Total Base Number, mgKOH/g, ASTM D2896	9.2
Viscosity Index, ASTM D2270	137

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims>

[/psims.aspx](#)

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2024

Terpel Comercial del Perú S.R.L.

Av. Jorge Basadre Grohmann 347,

Interior 1005, San Isidro

Lima, Perú

24 Horas emergencia en salud LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved