



MOBILGEAR™ EP SERIES

Mobil Industrial , Peru

Mobil Industrial

Product Description

Mobilgear EP lubricants are a family of industrial extreme pressure gear lubricants. They are formulated with mineral oils, which help reduce sludge formation, helping to increase oil service life.

Mobilgear EP gear oils are suitable for use wherever industrial gear oils are specified, and provide protection in applications where shock loading occurs.

Features and Benefits

Mobilgear EP oils can handle a variety of industrial gear applications.

Mobilgear EP gear oils offer the following benefits:

- EP wear protection of gears and bearings
- Resistance to sludge formation
- Improved oxidation resistance
- Applicable for use in splash or circulation systems

Applications

Mobilgear EP gear oils are suitable in a wide range of industrial spur, helical, bevel and steel-on-steel worm gearing, including drives for conveyers, agitators, dryers, fans, mixers, presses, pulpers, pumps, screens, extruders, and oil well pumps.

Properties and Specifications

Property	MOBILGEAR EP 150	MOBILGEAR EP 220	MOBILGEAR EP 320	MOBILGEAR EP 460
Grade	ISO 150	ISO 220	ISO 320	ISO 460
Copper Strip Corrosion, 3 h, 100 C, Rating, ASTM D130	1B	1B	1B	1B
EP Properties, Timken OK Load, lb, ASTM D2782	60	60	60	60
Emulsion, Time to 37 mL Water, 82 C, min, ASTM D1401	30	30	30	60
Flash Point, Cleveland Open Cup, °C, ASTM D92	208	274	276	>300
Four-Ball Extreme Pressure Test, Load Wear Index, kgf, ASTM D2783	42.5	42.5	42.5	42.5
Four-Ball Extreme Pressure Test, Weld Load, kgf, ASTM D2783	250	250	250	250

Property	MOBILGEAR 150 EP	MOBILGEAR 220 EP	MOBILGEAR 320 EP	MOBILGEAR 460 EP
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	15	18.9	24.1	30.4
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	152	220	320	455
Pour Point, °C, ASTM D97	-21	-18	-15	-12
Viscosity Index, ASTM D2270	99	96	96	96

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2022

Terpel Comercial del Perú S.R.L.

Av. Jorge Basadre Grohmann 347,

Interior 1005, San Isidro

Lima, Perú

24 Horas emergencia en salud LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil  

© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved