



Mobil DTE™ Oil 205

Mobil Industrial , Peru

Compressor Oil

Product Description

Mobil DTE Oil 205 is a lubricating oil formulated to provide excellent anti-wear and friction-reducing properties for compressor cylinder lubrication as well as protection against rust and corrosion. Mobil DTE Oil 205 is designed for wet-gas compression and exhibits excellent resistance to washing by water and other entrained liquids, resists oxidation and provides effective lubrication at low feed rates, thereby extending operating periods between valve cleaning intervals.

Features and Benefits

Mobil DTE Oil 205 offers the following benefits:

Features	Advantages and Potential Benefits
Excellent resistance to washing by water and other entrained liquids	Extended cylinder, ring, and packing life
Effective lubrication at low feed rates	Reduced oil purchases, extended valve rebuild intervals
Good anti-wear and friction reducing	Extended ring and packing life properties
Rust and corrosion protection	Extended compressor cylinder life
Resists oxidation	Reduced discharge valve deposits, extended valve rebuild intervals

Applications

Mobil DTE Oil 205 lubricant is recommended for the cylinder lubrication of reciprocating compressors and special rotary sliding vane compressors in air and inert service. It is particularly applicable where wet gas is being compressed. While developed primarily for multistage compressors, its superior qualities will provide benefits to many single- and two-stage compressors operating at higher pressures or discharge temperatures or when compressing wet gas.

Mobil DTE Oil 205 is not designed for use in compressor crankcases, particularly those compressors having high lead bearings, or crankshafts fitted with counterweights.

It should not be used when compressing air for breathing.

Properties and Specifications

Property	
Grade	ISO 220
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	19.5
Pour Point, °C, ASTM D97	-9
Density @ 15.6 C, kg/l, ASTM D4052	0.9
Flash Point, Cleveland Open Cup, °C, ASTM D92	282
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	220

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2023

Terpel Comercial del Perú S.R.L.

Av. Jorge Basadre Grohmann 347,

Interior 1005, San Isidro

Lima, Perú

24 Horas emergencia en salud

LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved