



Mobilcut Series

Mobil Industrial , Peru

Aqueous Metal Working Fluids

Product Description

Mobilcut is the trademark for Mobil Industrial lubricants line of high performance water miscible metal removal fluids. Formulated with leading edge base oils, additives and emulsifiers, the Mobilcut series of non-chlorinated products provides dependable performance in a wide array of metal removal processes. The products are designed to work in a variety of hard and soft water qualities and offer low foam potential and long-term corrosion protection for machine and component maintenance and inherently stable, Mobilcut products are designed for the modern machine shop where long service life, excellent machining performance and environmental concerns are important factors for increased productivity. These products are supplied in concentrated form and require mixing with water at the time of use.

Mobilcut 100 is a conventional milky soluble oil that readily mixes with different waters to form stable emulsions. Its versatile performance makes it suitable for a wide range of metal cutting and grinding operations for both ferrous and non ferrous materials where economical performance is the main consideration. It offers excellent emulsion stability and long-term corrosion protection for both components and machine tool.

Enhanced with lubricity agents, Mobilcut 140 is a long life water soluble fluid making it an ideal choice for moderate to heavy duty machining applications in the modern machine shop. It is formulated to provide long service life and good emulsion stability and durability while helping to increase tool life and surface finish, even in complex machining operations. Mobilcut 140 is an ideal choice where excellent machining performance is required for a wide variety of materials and applications while being easy to monitor and maintain.

Mobilcut 250 is a high performance semi-synthetic fluid formulated to enhance performance when machining aluminum and aluminum alloys and where low spark potential is important on sensitive components. Containing high levels of lubricity agents, it provides high machining performance of carbon and alloy steels and various metals.

Mobilcut 320 is a bio stable mineral oil synthetic cutting fluid which provides excellent residual corrosion protection, non-sticky residues and excellent separability from Mobil Vactra Oil Numbered series. It is designed for general grinding operations where a high quality surface finish, outstanding cooling and low foaming potential are the primary requirements. It will help maintain free and open grinding wheels for maximum performance and shows a marked stability for long service life.

Mobilcut 350 is a high performance, bio stable, synthetic (mineral oil free) fluid with outstanding tramp oil rejection and low foam properties.

Features and Benefits

The Mobilcut series of products are designed to help increase the productivity of modern machine shops by providing high performance features

Features	Advantages and Potential Benefits
Form stable emulsions and solutions	Ease of use and maintenance
Long term inherent stability	Increases batch life and reduces unpleasant odors
Low foaming potential	Improved performance even in high pressure systems
Resists formation of sticky residues	Improves machine cleanliness
High degree of corrosion protection	Reduces machine maintenance and rework of materials
Good separability from fines	Improves filterability and surface finish
Wide Range of applicability	Potential to consolidate products and reduce inventories
Compatible with high performance Mobil Vactra Oil No slideway lubricants	Easy separation and removal of tramp oil

Features	Advantages and Potential Benefits
Neutral Odor	Enhances the workplace environment

Applications

Mobilcut 100: General machining of easy to machine steels and copper alloys in light to moderate duty machining operations such as milling, turning, sawing, turning, drilling and reaming.

Mobilcut 140: Machining of aluminum and high machinability steels in moderate to heavy duty operations such as milling, turning, sawing, boring, drilling and reaming where the lubricity of a soluble oil is desired.

Mobilcut 250: Semi synthetic cutting fluid primarily intended for the machining of aluminum and aluminum alloys. It may also be used on a wide variety of ferrous materials where a more versatile fluid is required.

Mobilcut 320: Synthetic (mineral oil-free) fluid for grinding of steels and cast iron. Not suitable for Tungsten Carbide (Cobalt leaching).

Mobilcut 350: Synthetic (mineral oil-free) fluid for general cutting and grinding operations of ferrous materials from light to severe duty, designed for modern machine tool equipment and high surface finish.

Properties and Specifications

Property	100	140	250	320
Appearance, PTM 100		Amber Liquid	Dark Amber Liquid	Dark Green Liquid
Appearance, Visual	Slight Haze			
Cast Iron Corrosion, %BRKPT, PTM 108		3	3	2.5
Emulsion Type @ 3% in 50 ppm water, Rating, PTM 141			Semi-synthetic	Synthetic
Emulsion, Appearance, AMS 500.35-PROA	Milky White			
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	32			
Kinematic Viscosity at 40 C, cSt, PTM 143		59		
Pour Point, °C, ASTM D97	-10	-42		
Specific Gravity at 20 C, PTM 103		0.945	0.945	
Specific Gravity, 15.6 C/15.6 C, ASTM D4052	0.881			
pH at 3% in Distilled Water, PTM 104				9.4
pH at 5% in Distilled Water, PTM 104		9		
pH, Emulsion, 10% in Distilled Water, ASTM E70	10			

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2022

Terpel Comercial del Perú S.R.L.
Av. Jorge Basadre Grohmann 347,
Interior 1005, San Isidro
Lima, Perú
24 Horas emergencia en salud LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved