



Mobil Super Moto™ 3R 4T 20W-50

Mobil Passenger Vehicle Lube , Peru
High Performance Four-Stroke Motorcycle Engine Oil

Product Description

Mobil Super Moto™ 3R 4T 20W-50 is a high performance conventional four-stroke motorcycle engine oil primarily intended for general use in trike motorcycle formulated to protect against the high demands and high loads of trike motorcycle operating conditions.

Features and Benefits

Mobil Super Moto 3R 4T 20W-50 combines highly refined, quality mineral oils and an advanced additive system to provide good engine cleanliness, good protection and corrosion protection for trike motorcycle operating under severe conditions.

Key features and benefits include:

- Excellent features to protect trike motorcycles engines under severe conditions
- Good protection against wear that helps increase engine life
- Thermal and oxidation stability, which allows the oil to not oxidized rapidly and helps to keep engine cleanliness for smoother operation
- Excellent features to protect engine, clutch and transmission
- Good corrosion protection which helps to protect critical engine components

Features	Advantages and Potential Benefits
Good wear protection	Helps extend engine life
Thermal and oxidation stability	Helps keep engines clean to provide smoother operation
Good corrosion protection	Protects critical engine components

Applications

Mobil Super Moto 3R 4T 20W-50 is a high performance mineral oil, especially designed to protect trike motorcycles engines operating constantly under conditions.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SL
JASO MA2
JASO MA

Properties and Specifications

Property	
Grade	SAE 20W-50

Property	
Flash Point, °C, ASTM D92	233
Pour Point, °C, ASTM D97	-30
Ash, Sulfated, mass%, ASTM D874	0.75
Density @ 15 C, g/ml, ASTM D1298	0.8781
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	16.9
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	143.9

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2021
Terpel Comercial del Perú S.R.L.
Av. Jorge Basadre Grohmann 347,
Interior 1005, San Isidro
Lima, Perú
24 Horas emergencia en salud LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved