



Mobil Super™ Moto 4T MX 10W-30

Mobil Passenger Vehicle Lube , Peru

Semi-Synthetic High Performance Four-Stroke Motorcycle Engine Oil

Product Description

Mobil Super™ Moto 4T MX 10W-30 is a high performance semi-synthetic four-stroke motorcycle engine oil primarily intended for general use in many ty four-stroke motorcycles and engines. It's unique formulation provides excellent flow characteristics to reduce engine wear during start-up and outstanding protec the transmission and the clutch during operation. Its lower viscosity grade (SAE 10W-30) helps the engine to work at a higher level of efficiency, compared t 20W-50.

Features and Benefits

Mobil Super Moto 4T MX 10W-30 provides good engine cleanliness, good wear protection and corrosion protection. Key features and benefits include:

- Provides anti-wear protection to help promote long engine and transmission life
- Helps keep your engine cleaner
- Formulated with premium base stocks for increased oxidation stability and less volatility.
- Potential fuel economy compared with oil 20W-50 viscosity which can help reduce emissions.
- Excellent frictional properties for proper performance of the clutch.

Applications

Mobil Super 4T Moto MX 10W-30 oil is a product of an advanced blend of mineral and synthetic bases recommended for 4-stroke motorcycle in which the manufa specifies the use of SAE 10W-30. Its formulation provides the adequate level of protection for the engine transmission and clutch, particularly in air-cooled er which tend to operate at higher temperatures. It is also especially recommended for 4-stroke engines equipped with catalytic converters to reduce emissior recommended by ExxonMobil for applications requiring API SJ oils. Meets or exceeds the latest JASO MA performance standard.

Specifications and Approvals

This product meets or exceeds the requirements of:	
API SL	
JASO MA	
JASO MA	
JASO MA2	
JASO MA2	

Properties and Specifications

Property	
Grade	SAE 10W-30
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	68.35
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	10.4

Property	
Ash, Sulfated, mass%, ASTM D874	0.76
Pour Point, °C, ASTM D97	-35
Flash Point, Pensky-Martens Closed Cup, °C, ASTM D93	205

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2022
Terpel Comercial del Perú S.R.L.
Av. Jorge Basadre Grohmann 347,
Interior 1005, San Isidro
Lima, Perú
24 Horas emergencia en salud LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved