



## Mobil Super™ Gas 10W-30

Mobil Passenger Vehicle Lube , Peru

Premium Multigrade Passenger Vehicle Gas Engine Oils

### Product Description

Mobil Super™ Gas 10W-30 is a premium quality mineral gas motor oil meeting the latest industry engine oil specifications. Mobil Super Gas 10W-30 is especially designed for gas (VNG, LPG) and bi-fuel powered engines to provide a high level of performance and protection under most operating conditions.

### Features and Benefits

Mobil Super Gas 10W-30 is meticulously engineered for today's tougher engine specifications. It provides very good engine protection and helps promote long engine life.

- Enhanced thermal stability for high temperature conditions, which are common in gas powered engines
- Extended protection against engine wear and deposits formation
- Engine protection during start up
- Helps combat sludge

### Applications

Mobil Super Gas 10W-30 has been formulated to be suitable for use in nearly all vehicles. ExxonMobil particularly recommend Mobil Super Gas 10W-30 for daily driving under normal and long haul conditions:

- Nearly all gas and bi-fuel powered engine technologies
- Passenger cars, SUV's, light trucks and vans
- Normal Operating Conditions
- Suitable for use under a wide range of temperature conditions

### Specifications and Approvals

**This product is recommended for use in applications requiring:**

GM 6094M

**This product meets or exceeds the requirements of:**

API SP

ILSAC GF-6A

API SP Resource Conserving

API SN PLUS

API SN PLUS RESOURCE CONSERVING

This product meets or exceeds the requirements of:
API SN Resource Conserving
API SN
API SM
API SL
API SJ

### Properties and Specifications

Property	
Grade	SAE 10W-30
Viscosity Index, ASTM D2270	149
Density @ 15.6 C, g/ml, ASTM D4052	0.8581
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	10.3
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	64
Flash Point, Cleveland Open Cup, °C, ASTM D92	226
Pour Point, °C, ASTM D97	-39

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2021

Terpel Comercial del Perú S.R.L.

Av. Jorge Basadre Grohmann 347,

Interior 1005, San Isidro

Lima, Perú


24 Horas emergencia en salud      LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**



© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved