



## MOBIL SUPER GAS 25W50

Mobil Passenger Vehicle Lube , Peru

Gas and Bi-Fuel Engine Oils for High Mileage Engines

### Product Description

Mobil Super™ Gas 25W-50 is designed for gas powered engines to provide an excellent level of protection under the most demanding conditions.

Mobil Super Gas 25W-50 is a formula that is especially designed for engines with over 150,000 kilometers. The 25W-50 viscosity provides a thick oil film that helps protect gas converted engines (VNG, LPG) or bi-fuel powered engines that operate in severe service such as high temperatures and in city traffic where stop-and-go driving is common.

Mobil Super Gas 25W-50 is formulated from quality base stocks combined with performance additives, which help protect against the formation of sludge and corrosion.

### Features and Benefits

Mobil Super Gas 25W-50 helps:

- Reduce engine wear and corrosion in higher mileage vehicles
- Protect under a wide variety of operating conditions, especially high temperatures
- Flow more quickly and provide superior engine protection at low temperature start up when compared to high viscosity monogrades
- Reduce oil consumption
- Better thermal stability at high temperatures, which are common in gas powered engines
- Excellent high temperature stability, which allows the oil to not oxidized rapidly

### Applications

Mobil Super Gas 25W-50 is recommended for higher mileage vehicles. Before using Mobil Super Gas 25W-50, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API Service Classification.

### Specifications and Approvals

<b>This product is recommended for use in applications requiring:</b>
API CD
API SG

### Properties and Specifications

Property	
Grade	SAE 25W-50
Ash, Sulfated, mass%, ASTM D874	0.86
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	18.7

Property	
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	190.4
Flash Point, Cleveland Open Cup, °C, ASTM D92	234
Pour Point, °C, ASTM D97	-21
Density @ 15.6 C, g/ml, ASTM D4052	0.8966

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

Terpel Comercial del Perú S.R.L.

Av. Camino Real 456,

Torre Real Piso 14 San Isidro

Lima Perú

24 Horas emergencia en salud      LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon   Mobil   ESSO   XTO

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved