



Mobil Super™ 3000 Formula R 5W-30

Mobil Passenger Vehicle Lube , Peru

High Performance Engine Oil

Product Description

Mobil Super 3000 Formula R 5W-30 is high-performance very low ash engine oil designed to help prolong the life and maintain the efficiency of the Exhaust Car Emission Reduction Systems in both diesel and gasoline powered automobiles.

Features and Benefits

- Helps to maintain the efficiency of the Exhaust Emission Reduction systems in both diesel and gasoline vehicles.
- Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown.
- Provides excellent fluidity at low temperatures allowing easy winter starting and rapid oil circulation around the engine.
- Suitable for use in both gasoline and diesel engine passenger car and light commercial vehicles.

Specifications and Approvals

This product has the following approvals:

FIAT 9.55535-S4

RENAULT RN0720

This product is recommended for use in applications requiring:

FIAT FIAT 9.55535-S4

This product meets or exceeds the requirements of:

ACEA C4-16

Properties and Specifications

Property	
Grade	SAE 5W-30
Phosphorus, mass%, ASTM D4951	0.07
Flash Point, Pensky-Martens Closed Cup, °C, ASTM D93	200
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	68

Property	
Pour Point, °C, ASTM D97	-36
Density @ 15 C, g/ml, ASTM D1298	0.85
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	12
Flash Point, Cleveland Open Cup, °C, ASTM D92	236
Ash, Sulfated, mass%, ASTM D874	0.5

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2021

Terpel Comercial del Perú S.R.L.

Av. Camino Real 456,

Torre Real Piso 14 San Isidro

Lima Perú

24 Horas emergencia en salud LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com. ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved