



Mobil Super Moto™ Gas 4T 20W-50

Mobil Passenger Vehicle Lube , Peru

High Performance Four-Stroke Motorcycle and Trike Motorcycle Gas and Bi-Fuels Engine Oil

Product Description

Mobil Super Moto™ Gas 4T 20W-50 is a high performance conventional four-stroke motorcycle gas engine oil primarily intended for general use in trike motorcycles. It is formulated to provide enhanced protection for the high demands posed on trike motorcycles. Mobil Super Gas 4T 20W-50 is especially designed for gas (VNG, LPG) and bi-fuel powered motorcycle engines to provide an excellent level of protection and performance under the most demanding conditions.

Features and Benefits

Mobil Super Moto Gas 4T 20W-50 combines highly refined, quality mineral oils and an advanced additive system to provide good engine cleanliness, good wear protection and corrosion protection. Key features and benefits include:

- Excellent features to protect trike motorcycles engines under severe conditions
- Enhanced thermal stability against high temperatures generated in gas powered engines
- Good protection against wear that helps increase engine life
- Thermal and oxidation stability, which allows the oil to not oxidized rapidly and helps to keep engine cleanliness for smoother operation
- Excellent features to protect engine, clutch and transmission
- Good corrosion protection which helps to protect critical engine components

| Features | Advantages and Potential Benefits |
|---------------------------------|--|
| Good wear protection | Helps extend engine life |
| Thermal and oxidation stability | Helps keep engines clean to provide smoother operation |
| Good corrosion protection | Protects critical engine components |

Applications

Mobil Super Moto Gas 4T 20W-50 is a high performance mineral gas motor oil that has been especially designed to provide enhanced protection for the high demands of trike motorcycles.

Specifications and Approvals

| This product meets or exceeds the requirements of: |
|--|
| API SL |
| JASO MA2 |
| JASO MA |

Properties and Specifications

| Property | |
|--|------------|
| Grade | SAE 20W-50 |
| Flash Point, °C, ASTM D92 | 233 |
| Pour Point, °C, ASTM D97 | -30 |
| Ash, Sulfated, mass%, ASTM D874 | 0.75 |
| Density @ 15 C, g/ml, ASTM D1298 | 0.88 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 16.9 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 143.9 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2021

Terpel Comercial del Perú S.R.L.

Av. Jorge Basadre Grohmann 347,

Interior 1005, San Isidro


Lima, Perú

24 Horas emergencia en salud LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved