



Mobil Super™ Sintetico 5W-30

Mobil Passenger Vehicle Lube , Peru

100% Synthetic Engine Oil

Product Description

Mobil Super™ Sintetico 5W-30 is a high-performance, low-ash, 100% synthetic engine oil designed to help extend engine life and maintain the effectiveness of exhaust emission reduction systems in passenger cars, light commercial vehicles, and vans with diesel and gasoline engines.

This product is recommended for use in Mercedes vehicles and a wide range of European cars and light commercial vehicles with oil specifications based on the industry's ACEA C3 and/or API SP base standards.

Features and Benefits

Mobil Super™ Sintetico 5W-30 helps maintain the efficiency of diesel and gasoline vehicle exhaust emission reduction systems.

- Allows prolonged operation at elevated temperatures without oxidative oil thickening or degradation
- Provides excellent fluidity at low temperatures, allowing for easy starting in the winter and rapid oil circulation around the engine
- Long-term engine protection against wear and accumulation of sludge and deposits
- Suitable for use in passenger cars and light commercial vehicles with both petrol and diesel engines

Applications

Mobil Super™ Sintetico 5W-30 has been developed to meet the latest engine oil specifications required by major automotive manufacturers and is compatible with the latest diesel and gasoline engine particulate filters and all catalytic converters.

Mobil Super™ Sintetico 5W-30 is specially recommended by ExxonMobil for use in:

- Passenger cars and light commercial vehicles or vans of the Mercedes brand. This engine oil is also recommended for many passenger cars, light commercial vehicles, or vans that require ACEA C3 and/or API SN
- Gasoline and diesel engines with diesel particulate filters (DPFs) and catalytic converters
- Normal to occasionally severe operating conditions, including city driving conditions

Always check your owner's manual to check the recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:

BMW Longlife 04

MB-Approval 229.52

MB-Approval 229.51

RENAULT RN0710

RENAULT RN0700

This product meets or exceeds the requirements of:

API SN

API SN PLUS

API SP

API SP Resource Conserving

ILSAC GF-6A

ACEA C3

Properties and Specifications

| Property | |
|--|-----------|
| Grade | SAE 5W-30 |
| Pour Point, °C, ASTM D97 | -42 |
| Phosphorus, mass%, ASTM D4951 | 0.08 |
| Density @ 15 C, g/ml, ASTM D4052 | 0.85 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 12.2 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 61.0 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 244 |
| Ash, Sulfated, mass%, ASTM D874 | 0.73 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2023

Terpel Comercial del Perú S.R.L.

Av. Jorge Basadre Grohmann 347,

Interior 1005, San Isidro

Lima, Perú

24 Horas emergencia en salud LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved