



## Mobil 1™ 5W-30

Mobil Passenger Vehicle Lube , French Polynesia

Advanced Full Synthetic Engine Oil

### Product Description

Mobil 1™ Triple Action Power advanced full synthetic engine oil delivers outstanding engine Performance, Protection, and Cleanliness.

### Features and Benefits

Why these matter for your engine:

- **PERFORMANCE:** Reduces the stress of daily wear and harsh conditions for longer engine life.
- **PROTECTION:** Guards against extreme temperatures to prevent breakdowns.
- **CLEANLINESS:** Prevents buildup of contaminants and sludge for a cleaner engine.

Mobil 1™ Triple Action Power is feature packed to:

- **PERFORM:** Keeps your engine running like new.
- **PROTECT:** 10X\* better protection for high temperatures.
- **CLEAN:** Fights sludge with active cleaning agents.

\*Based on Sequence IIIH, against API SP specification

### Applications

Mobil 1™ Triple Action Power is suitable for use in petrol, diesel, and hybrid vehicles.

Always check your owner's manual for the recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

This product has the following approvals:
HONDA/ACURA HTO-06

This product is recommended for use in applications requiring:
Ford WSS-M2C929-A
Ford WSS-M2C946-A
Ford WSS-M2C946-B1
FIAT 9.5535-CR1

**This product meets or exceeds the requirements of:**

FORD WSS-M2C961-A1

Chrysler MS-6395

CHRYSLER MS-13340

API SP Resource Conserving

API SP

API SN PLUS

API SN

API SM

ILSAC GF-6A

ACEA A5/B5

ACEA C2

**Properties and Specifications**

Property	
Grade	SAE 5W-30
Total Base Number, mgKOH/g, ASTM D2896	9.2
Ash, Sulfated, mass%, ASTM D874	0.76
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	61
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	10.3
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	13700
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	235
Density @ 15.6 C, g/ml, ASTM D4052	0.852
Viscosity Index, ASTM D2270	157

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2023

**ExxonMobil**



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved