



Mobil Super Moto™ 10W30 15W40 20W40 20W50

Mobil Passenger Vehicle Lube , Philippines

High Performance Four-Stroke Motorcycle Engine Oil

Product Description

Mobil Super Moto™ 10W-30, 15W-40, 20W-40 and 20W-50 are high performance conventional four-stroke motorcycle engine oils primarily intended for general use in all types of four-stroke motorcycles and engines.

Features and Benefits

Mobil Super Moto 10W-30, 15W-40, 20W-40 and 20W-50 combine highly refined, quality mineral oils and an advanced additive system to provide good engine cleanliness, good wear protection and corrosion protection. Motorcycle engine oils protect engine and gear and make clutch working.

Key features and benefits include:

| Features | Advantages and Potential Benefits |
|---------------------------------|---|
| Good wear protection | Helps extend engine life |
| Thermal and oxidation stability | Helps keep engines clean for smoother operation |
| Good corrosion protection | Protects critical engine components |
| Broad viscosity range | Year round engine protection and performance |

Specifications and Approvals

| Mobil Super Moto meets or exceeds the requirements of: | 10W-30 | 15W-40 | 20W-40 | 20W-50 |
|--|--------|--------|--------|--------|
| API | SL | SL | SL | SL |
| JASO | MA2 | MA2 | MA2 | MA2 |

Typical Properties

| Mobil Super Moto | 10W-30 | 15W-40 | 20W-40 | 20W-50 |
|------------------------------|--------|--------|--------|--------|
| SAE Grade | 10W-30 | 15W-40 | 20W-40 | 20W-50 |
| Viscosity, ASTM D445 | | | | |
| cSt @ 40°C | 71 | 99 | 122 | 185 |
| cSt @ 100°C | 10.5 | 13.7 | 15 | 20.5 |
| Sulfated Ash, wt%, ASTM D874 | 0.8 | 0.8 | 0.8 | 0.8 |
| Pour Point, °C, ASTM D97 | -25 | -30 | -30 | -33 |

| Mobil Super Moto | 10W-30 | 15W-40 | 20W-40 | 20W-50 |
|--------------------------------|--------|--------|--------|--------|
| Flash Point, °C, ASTM D92 | 220 | 230 | 230 | 230 |
| Density @15°C g/ml, ASTM D4052 | 0.88 | 0.88 | 0.88 | 0.88 |

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.
07-2021

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved