



Mobil Super Moto™ 10W-40

Mobil Passenger Vehicle Lube , Pacific Islands

Superior Performance Four-Stroke Motorcycle Engine Oil

Product Description

Mobil™Super Moto 10W-40 is a high performance, synthetic blend technology four-stroke motorcycle engine oil developed to provide boosted engine cleanline protection for all types of motorcycles and operation.

Features and Benefits

Mobil Super Moto 10W-40 combines a unique blend of high quality mineral and synthesised hydrocarbon baseoils together with an advanced additive system to p excellent engine cleanliness, wear protection and effective corrosion prevention. Motorcycle engine oil protects engine and gear and make clutch working.

Features	Advantages and Potential Benefits
Excellent wear protection	Longer engine component and overall engine life
Good thermal , oxidation stability and deposit control	Cleaner running engines resulting in smooth flawless operation
Excellent corrosion protection properties	Longer life of valve train and bearing components
Enhanced low temperature properties	Easier cold weather starting, longer electrical system life

Applications

Mobil Super Moto 10W-40 is specifically recommended for lubrication of all types of four-stroke motorcycle engines, where the latest industry standard qualit required.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SL
JASO MA
JASO MA2

Properties and Specifications

Property	
Grade	SAE 10W-40
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14.4
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	100
Viscosity Index, ASTM D2270	150
Ash, Sulfated, mass%, ASTM D874	0.8

Property	
Pour Point, °C, ASTM D97	-30
Flash Point, Cleveland Open Cup, °C, ASTM D92	230
Density @ 15 C, kg/l, ASTM D4052	0.87

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2022
Mobil International Petroleum Corporation
Tour Cogimpa - 19 Avenue Foch,
BP 108, 98845 Noumea Cedex
Nouvelle Calédonie

+687 24 21 50

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved