



## Mobil Super 2000 Series

Mobil Passenger Vehicle Lube , Pacific Islands

Premium Semi-Synthetic Passenger Vehicle Engine Oil

### Product Description

The Mobil Super 2000 range of lubricants are enhanced-premium semi-synthetic engine oils, designed to provide an excellent level of protection and performance.

### Features and Benefits

Mobil Super 2000 products are industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super 2000 5W-20 and 5W-30 contain low friction semi-synthetic formulation which increases engine efficiency and offers greater fuel economy.

Mobil Super 2000 provides:

- Excellent wear protection
- Excellent engine cleanliness
- Excellent high temperature protection
- Excellent fuel economy (for SAE 5W-20 and 5W-30)

### Applications

Mobil Super 2000 products are formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Latest engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal to occasionally severe operating conditions
- Turbo-Chargers
- High Performance Engines
- Stop and Go City Driving

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

This product is recommended by ExxonMobil for use in applications requiring:	5W-20	5W-30	10W-30
API CF	X		
ILSAC GF-4	X		X

This product is recommended for use in applications requiring:	5W-20	5W-30	10W-30
API CF		X	

This product is recommended for use in applications requiring:	5W-20	5W-30	10W-30
API Energy Conserving (SM)		X	
ILSAC GF-4		X	

This product meets or exceeds the requirements of:	5W-20	5W-30	10W-30
API SJ		X	X
API SL		X	X
API SM	X	X	X
API SN	X	X	X
API SN Resource Conserving		X	X
Chrysler MS-6395		X	

### Properties and Specifications

Property	5W-20	5W-30	10W-30
Grade	SAE 5W-20	SAE 5W-30	SAE 10W-30
Ash, Sulfated, mass%, ASTM D874	0.8	0.8	0.82
Density @ 15 C, g/ml, ASTM D4052	0.85	0.86	0.8665
Flash Point, Cleveland Open Cup, °C, ASTM D92	220	220	220
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	2.6		3.14
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	8.5	10.5	10.4
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	48	62	66.3
Pour Point, °C, ASTM D97	-30	-33	-33
Viscosity Index, ASTM D2270	155	160	145

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2021

Mobil International Petroleum Corporation  
 Tour Cogimpa - 19 Avenue Foch,  
 BP 108, 98845 Noumea Cedex  
 Nouvelle Calédonie

+687 24 21 50

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil Esso XTO

© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved