



Mobil Delvac 1330, 1340, 1350

Mobil Commercial Vehicle Lube, Pakistan

Heavy Duty Diesel Engine Oils

Product Description

Mobil Delvac 1330, 1340, and 1350 are high performance, heavy duty diesel engine oils formulated from advanced technology base oils and a balanced additive system. They are specifically engineered for performance in intercooled, turbo-charged engines operating under severe on and off highway conditions. Mobil Delvac 1300 monogrades are used in a wide range of applications where a monograde lubricant is recommended.

Features and Benefits

| Features | Advantages and Potential Benefits |
|--|--|
| Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion | Prolonged engine life Less wear Excellent protection against ring sticking |
| Extended TBN reserve | Long-term deposit/wear control |

Applications

- Naturally aspirated and turbo-charged diesel powered equipment
- On highway light and heavy duty trucking
- Off highway industries including: construction, mining, quarrying, and agriculture

Specifications and Approvals

| Mobil Delvac 1300 Monogrades are recommended for use in applications requiring: | Mobil Delvac 1330 | Mobil Delvac 1340 | Mobil Delvac 1350 |
|---|-------------------|-------------------|-------------------|
| API CF/SF | X | X | X |
| Daimler Chrysler MB 227.0 | X | X | |

Other Qualifications

| Product Name Claim | Mobil Delvac 1330 | Mobil Delvac 1340 | Mobil Delvac 1350 |
|--------------------|-------------------|-------------------|-------------------|
| 10 TBN minimum | X | X | X |

Typical Properties

| Mobil Delvac 1300 Monogrades | 1330 | 1340 | 1350 |
|------------------------------|------|------|------|
| SAE Grade | 30 | 40 | 50 |
| Viscosity, ASTM D 445 | | | |
| cSt @ 40°C | 106 | 146 | 231 |
| cSt @ 100°C | 11.8 | 14.6 | 19.9 |

| Mobil Delvac 1300 Monogrades | 1330 | 1340 | 1350 |
|-------------------------------------|------|------|------|
| Viscosity Index, ASTM D 2270 | 99 | 99 | 99 |
| Sulfated Ash, wt%, ASTM D 874 | 1.1 | 1.1 | 1.1 |
| Total Base #, mg KOH/g, ASTM D 2896 | 10.1 | 10.1 | 10.1 |
| Pour Point, °C, ASTM D 97 | -21 | -21 | -18 |
| Flash Point, °C, ASTM D 92 | 256 | 254 | 260 |
| Density @ 15°C kg/l, ASTM D 4052 | 0.89 | 0.90 | 0.90 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Delvac 1300 are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

04-2023

Mobil Askari Lubricants Limited

D-46, Block-5

KDA Scheme-5, Clifton

Karachi, Pakistan

Phone: (92-21) 111-840-840 Fax : (92-21) 583-1013 and 583-0082

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved