



Mobil Delvac™ AK 950

Mobil Commercial Vehicle Lube , Pakistan

Heavy Duty Diesel Engine Oil

Product Description

Mobil Delvac™ AK 950 is heavy-duty, mono-grade diesel engine oil formulated with an optimised base oil and additive system.

Features and Benefits

Features	Advantages and Potential Benefits
<ul style="list-style-type: none"> Protection against rust and corrosion 	<ul style="list-style-type: none"> Protects equipment and helps to reduce operating costs
<ul style="list-style-type: none"> Thermal and oxidation stability 	<ul style="list-style-type: none"> Controls sludge build-up and deposits

Applications

- Diesel and gasoline powered equipment where API CD level performance is required.
- On-highway light and medium duty trucking.
- Off-highway industries including construction, mining, quarrying and agriculture.

Specifications and Approvals

This product is recommended for use in applications requiring:
API CD

Properties and Specifications

Property	
Grade	SAE 50
Density @ 15 C, g/ml, ASTM D1298	0.896
Ash, Sulfated, mass%, ASTM D874	0.7
Flash Point, Cleveland Open Cup, °C, ASTM D92	235
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	19
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	220
Pour Point, °C, ASTM D97	-18
Total Base Number, mgKOH/g, ASTM D2896	5
Viscosity Index, ASTM D2270	97

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020

Mobil Askari Lubricants Limited

D-46, Block-5

KDA Scheme-5, Clifton

Karachi, Pakistan

Phone: (92-21) 111-840-840 Fax : (92-21) 583-1013 and 583-0082

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved