

Mobil Special™ 20W-50

Mobil Passenger Vehicle Lube, Pakistan

High Performance Motor Oil

Product Description

Mobil Special™ 20W-50 is a high performance motor oil for all types of vehicles. Mobil Special 20W-50 delivers engine protection and cleanliness. Mobil Special 20W-50 is recommended for use in a wide range of applications and operating conditions.

Features and Benefits

- Helps reduce engine wear and corrosion
- Helps keep engine clean
- Multigrade motor oil allowing easier starts at low temperatures
- Good high temperature properties

Specifications and Approvals

Recommended by	ExxonMobil for Use in Applications Requiring:
TACCONTINUCTOCO D	Locolinatorii of osciila pricodolis recognilio.

API SG

API CD

Typical Properties

Mobil Special 20W-50	Test Method	Unit	
SAE Grade			20W-50
Appearance	Visual		Bright and Clear
Viscosity @ 100°C	ASTM D445	cSt	17.2
CCS Viscosity @ -20°C	ASTM D5293	сР	7224
Sulfated Ash	ASTM D874	wt%	1.0
Total Base Number (TBN)	ASTM D2896	mg KOH/g	8.2
Flash Point	ASTM D92	°C	230
Pour Point	ASTM D97	°C	-24

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application, following the recommendations provided in the Material Safety Data Sheet (MSDS). MSDSs are available upon request through your sales contract office, or via the Internet on http://www.exxonmobil.com. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

09-2022

Mobil Askari Lubricants Limited

D-46, Block-5 KDA Scheme-5, Clifton Karachi, Pakistan

Phone: (92-21) 111-840-840 Fax: (92-21) 583-1013 and 583-0082

http://www.exxonmobil.com

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

