



**Mobil™ Brake Fluid DOT 4**

Mobil Passenger Vehicle Lube , Pakistan

Extra High Performance Hydraulic Brake Fluid

## Product Description

Mobil Brake Fluid DOT 4 is an extra high performance hydraulic brake fluid for use in automotive disc, drum and anti-skid brake systems and clutch systems.

## Features and Benefits

Mobil Brake Fluid DOT 4 is based on polyethylene glycol ether technology to provide the highest level of brake and clutch performance in modern as well as older automotive and commercial vehicles. Key features and benefits include:

Features	Advantages and Potential Benefits
High boiling point	Consistent and safe brake performance under severe braking pressure
Minimum rubber component swell	Reduces leakage and loss of fluid to a minimum
Excellent corrosion protection	Extended life and reliability of brake system components

## Applications

Mobil Brake Fluid DOT 4 is recommended by ExxonMobil for use in applications requiring disc, drum and anti-skid braking systems used in average to high performance vehicles requiring DOT 3 or DOT 4 level performance. Recommendations for use include:

- Use only in its concentrated form out of a previously unopened or well sealed container
- Always seal the container immediately after use as the fluid absorbs moisture from the atmosphere quite rapidly; this will reduce service life significantly.
- Never reuse drained brake fluid.
- Brake fluid can affect the vehicle paintwork, so remove spills immediately without rubbing.
- Brake fluid should be drained from the vehicle every two years or 40,000 Km (24,000 Miles) and refilled.
- Check Owners Operators Manual for details.

## Specifications and Approvals

This product meets or exceeds the requirements of the following industry specification:
FMVSS 116 DOT 3
FMVSS 116 DOT 4
ISO 4925:2005 Class 3
ISO 4925:2005 Class 4
SAE J1703
SAE J1704

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2022

Mobil Askari Lubricants Limited

D-46, Block-5

KDA Scheme-5, Clifton

Karachi, Pakistan

Phone: (92-21) 111-840-840 Fax : (92-21) 583-1013 and 583-0082

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved