



Mobil Delvac City Logistics M 5W-30

Mobil Commercial Vehicle Lube , Poland

Synthetic Light Commercial Vehicle Engine Oil

Product Description

Mobil Delvac™ City Logistics M 5W-30 is a low ash synthetic engine oil that provides long engine life and excellent engine protection against sludge and wear.

Mobil Delvac™ City Logistics M 5W-30 provides excellent lubrication of diesel and gasoline engines operating in severe driving conditions typically encountered in city operations. This product is recommended by ExxonMobil for European engines for use in a wide range of light-duty commercial vehicles like Mercedes vans or other vans requiring ACEA C3.

Features and Benefits

Mobil Delvac™ City Logistics M 5W-30 is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in recent diesel and gasoline engines as well as older models: It is fully compatible with most Diesel Particulate Filters and Catalytic Convertors. Key benefits include:

| Features | Advantages and Potential Benefits |
|--|---|
| Increased thermal and oxidation stability | Help to reduced sludge build-up, deposits, and long oil and engine life |
| Enhanced wear protection | Helps towards long component and engine life |
| Advanced piston deposit control | Helps to keep engines clean with reduced maintenance costs and long engine life |
| Advanced soot handling to control viscosity increase, sludge build up, and filter pressure | Helps to enhance engine protection for long engine life |
| Enhanced low temperature pumpability | Fast start up with reduced wear operating in low temperature climates |
| Stayed in viscosity grade | Helps to maintain fuel economy |

Applications

ExxonMobil recommends Mobil Delvac™ City Logistics M 5W-30 for demanding driving conditions:

- Mercedes-Benz light commercial vehicles (it meets the needs of the engine requirements of the MB group when requiring a MB 229.31, 229.51 or 229.52 approved product)
- Light commercial vehicles or vans requiring ACEA C3
- Volkswagen light commercial vehicles requiring VW 505 00/505 01 approved product.
- Gasoline and Diesel with Diesel Particulate Filters (DPF) &and Catalytic Convertors
- Normal to occasionally severe operating conditions (including city driving conditions)
- Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

MOBIL DELVAC CITY LOGISTICS M 5W-30 meets or exceeds the requirements of:

API SN

This product has the following builder approvals:

MB-Approval 229.31

MB-Approval 229.51

MB-Approval 229.52

VW 505 00

VW 505 01

This product meets or exceeds the requirements of:

ACEA C3

API SM

API SL

Properties and Specifications

| Property | |
|--|-----------|
| Grade | SAE 5W-30 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 11.9 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 68 |
| Ash, Sulfated, mass%, ASTM D874 | 0.8 |
| Total Base Number, mgKOH/g, ASTM D2896 | 7.4 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 230 |
| Density @ 15 C, g/ml, ASTM D4052 | 0.85 |
| Pour Point, °C, ASTM D97 | -36 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2021

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BV.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

ExxonMobil Poland sp. z o.o.
ul. Chmielna 85/87
00-805 Warszawa

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.pl/pl-pl/contact-us>

Tel +48 22 556 29 00
Fax +48 22 620 16 61

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved