



## Mobiltrans HD Series

Mobil Commercial Vehicle Lube , Papua New Guinea

Heavy Duty Transmission and Drivetrain Lubricants

### Product Description

Mobiltrans HD 10W, 30, 50, and 60 are extra high performance, heavy duty transmission and drive-train lubricants engineered to meet or exceed the requirements of the rigorous Caterpillar TO-4 specification. This product line is uniquely designed to optimise the performance of powershift transmissions, gearboxes, and final drives. In hydraulic applications, they provide maximum protection even in high pressure systems

This technology combines selected base oils and an advanced additive system to deliver the precise performance parameters needed to maximise the productivity of construction, quarrying, and mining equipment operating in severe conditions. These products offer a clear performance advantage over the use of mixed fleet engine oils and previously used lubricants meeting Caterpillar TO-2.

### Applications

Recommended by ExxonMobil for use in:

- Heavy duty transmissions, gear boxes, final drives, and hydraulic systems used in off-highway applications
- Off-highway industries including: mining, construction, quarrying, and agriculture
  - Manual, powershift, and automatic transmissions where Allison C-4 fluids (SAE 10W and 30 grades) are called for including Twin Disc and transmissions calling for Type F fluids
- Most mobile equipment hydraulic applications

### Specifications and Approvals

| This product has the following approvals: | 30 | 50 | 60 | 10W |
|---|----|----|----|-----|
| ZF TE-ML 03C                              | X  |    |    | X   |
| ZF TE-ML 07F                              | X  |    |    |     |

| This product is recommended for use in applications requiring: | 30 | 50 | 60 | 10W |
|--|----|----|----|-----|
| Allison C-4  | X  |    |    | X   |
| KOMATSU KES 07.868.1   | X  | X  |    | X   |

| This product meets or exceeds the requirements of: | 30 | 50 | 60 | 10W |
|--|----|----|----|-----|
| CATERPILLAR TO-4                                   | X  | X  | X  | X   |

### Properties and Specifications

| Property | 30     | 50     | 60     | 10W     |
|----------|--------|--------|--------|---------|
| Grade    | SAE 30 | SAE 50 | SAE 60 | SAE 10W |

| Property   | 30   | 50   | 60   | 10W  |
|--|------|------|------|------|
| Density @ 15 C, kg/l, ASTM D4052                           | 0.89 | 0.91 | 0.91 | 0.89 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92              | 224  | 240  | 244  | 202  |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 11.2 | 18   | 25.2 | 6.3  |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 100  | 195  | 340  | 42   |
| Pour Point, °C, ASTM D97                                   | -18  | -15  | -12  | -33  |
| Viscosity Index, ASTM D2270                                | 97   | 100  | 96   | 96   |

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2023

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved