



Mobil™ ATF 220 Syn Tech

Mobil Passenger Vehicle Lube , Papua New Guinea

Automatic Transmission Fluid

Product Description

Mobil™ ATF 220 Syn Tech is a high performance fluid for automatic transmissions in vehicles requiring Dexron II/IID. It is also used as a hydraulic fluid in applications.

Features and Benefits

Mobil ATF 220 Syn Tech is formulated from high-quality conventional base oils combined with a special additive system including viscosity index improvers, antiox and defoaments providing smooth and controlled friction/wear characteristics. The product provides consumers an excellent driving experience even in broad range driving conditions in a wide variety of automobiles requiring Dexron II/IID specifications.

Features	Advantages and Potential Benefits
Good thermal and oxidation stability	Resists lacquer, sludge and deposit formation to keeps transmissions clean for efficient operation over the full life
Good anti-wear properties	Meets the wear requirement to promote longer transmission life
Excellent low-temperature fluidity	Assist in improved start-up and clean fast lubrication at low ambient temperatures
Effective foam control properties	Smooth and lasting shift feel and reduced fluid loss in severe service-operating conditions
Compatible with all common seal materials used in Type IID transmissions	Maintains effective leakage control

Applications

Mobil ATF 220 Syn Tech is recommended for some automatic and manual transmissions in passenger cars and light trucks specifying Dexron II/IID level performance as well as the related power steering systems. It is also suitable for use in some special hydraulic systems in farm equipment and other installations having similar requirements. It is recommended that the user consult the manufacturer's requirements. Other applications include:

- Off-highway transmissions power steering and other hydraulic systems.
- Industrial hydraulic systems and components.

Specifications and Approvals

This product is recommended for use in applications requiring:
Ford ESR-M2C163-A2
GM DEXRON II
GM DEXRON IID
GM Type A Suffix A
MB 236.7

This product is recommended for use in applications requiring:
R. Bosch AS TE-ML 09

Properties and Specifications

Property	
Flash Point, Cleveland Open Cup, °C, ASTM D92	229
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	40.5
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	7
Pour Point, °C, ASTM D97	-42
Color, Visual	Red
Density @ 15 C, g/cm3, ASTM D4052	0.8624
Viscosity Index, ASTM D2270	131
Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983	41200

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2023

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved