



## Mobil Super™ 2000 5W-30

Mobil Passenger Vehicle Lube , Papua New Guinea

### Product Description

Mobil Super 2000 5W-30 is an enhanced-premium semi-synthetic motor oil meeting the latest industry engine oil specifications. It is designed to provide an excellent level of protection and performance under the most demanding conditions.

### Features and Benefits

Mobil Super 2000 products are industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super 2000 5W-30 contains low friction semi-synthetic formulation which increases engine efficiency and offers greater fuel economy. Mobil Super 2000 5W-30 helps to promote long engine life.

Mobil Super 2000 5W30:

- Its additive package provides excellent protection against engine wear and deposit formation.
- Provides superior engine protection during start up
- Excellent high temperature protection thanks to its high quality base oil formulation

### Applications

Mobil Super 2000 5W-30 product is formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Latest gasoline engine technologies
- Passenger cars, SUV's, light trucks and vans
- Normal to severe operating conditions
- Turbo-Chargers
- High Performance Engines

### Specifications and Approvals

**This product is recommended for use in applications requiring:**

Ford WSS-M2C915-A

GM 6094M

**This product meets or exceeds the requirements of:**

API SN

API SM

Ford WSS-M2C929-A

Ford WSS-M2C946-A

**This product meets or exceeds the requirements of:**

Chrysler MS-6395

API SN Resource Conserving

**Properties and Specifications**

Property	
Grade	SAE 5W-30
Appearance, AMS 1738	Clear and Bright
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	10.6
Odor, AMS 1695	PASS
Cold-Cranking Simulator, Apparent Viscosity @ -30 C, mPa.s, ASTM D5293	5730
Pour Point, °C, ASTM D97	-36
Total Base Number, mgKOH/g, ASTM D2896	8.2
Viscosity Index, ASTM D2270	157
Flash Point, Cleveland Open Cup, °C, ASTM D92	227
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	63.6
Mini-Rotary Viscometer, Yield Stress, -35 C, Pa, ASTM D4684	16900
Density @ 15 C, g/ml, ASTM D4052	0.8605

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2023




© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved