



Mobil Delvac Legend™ 25W-50 High Mileage

Mobil Commercial Vehicle Lube , Puerto Rico

High Performance Diesel Engine Oil

Product Description

Mobil Delvac Legend 25W-50 Alta Viscosidad, high performance diesel engine oil that provides proven protection for diesel engines operating in severe applications. Mobil Delvac 25W-50 Alta Viscosidad is recommended for use in a wide range of heavy-duty applications and operating environments found in trucking, mining, construction, quarrying, and agricultural industries.

Features and Benefits

More than 90 year of experience and innovation supports the technology in Mobil Delvac Legend 25W-50 Alta Viscosidad. Delivers excellent performance in both naturally aspirated as well as turbo-charged diesel powered equipment. The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
TBN reserve	Deposit control and acid neutralization
High Viscosity and Stay-in-grade shear stability	Reduced oil consumption, increased wear protection and high oil pressure across a wide operating temperature range
Excellent detergency/dispersancy	Cleaner engines and prolonged engine life
Component compatibility	Long gasket and seal life

Applications

- Naturally aspirated and turbo-charged diesel powered equipment European, Japanese, and American manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture

Specifications and Approvals

This product is recommended for use in applications requiring:
API CF-4

Properties and Specifications

Property	
Grade	SAE 25W-50
Viscosity Index, ASTM D2270	116
Flash Point, Cleveland Open Cup, °C, ASTM D92	250

Property	
Density @ 15 C, g/ml, ASTM D1298	0.89
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	18.7
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	181.5
Pour Point, °C, ASTM D97	-27

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil

Exxon

Mobil

Esso

XTREME

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved