



Mobilube™ S 80W-90

Mobil Commercial Vehicle Lube , Portugal

Multi-Purpose Drivetrain Lubricant

Product Description

Mobilube™ S 80W-90 is an extra high performance drivetrain lubricant engineered to provide excellent lubrication for state-of-the-art, heavy duty manual transn components used in on-highway commercial vehicles and cars. Potential benefits include excellent shifting performance, good low temperature fluidity, an temperature viscosity retention. Mobilube S 80W-90 provides API GL-4/5 level performance.

Features and Benefits

Today's technology has vastly improved the performance capabilities of on-highway vehicles in terms of load, speed, and control through inno-drivetrain designs. designs have increased the requirements of components and lubricants to deliver a higher level of performance. For heavy-duty applications, friction control reduction, thermal stability, shear stability, rust and corrosion inhibition, and seal protection are features that must be optimally balanced to contribute to long ge synchroniser life, smooth shift control, fuel economy, and high load capability over a wide range of applications. Mobilube S 80W-90 delivers outstanding perform: current as well as older units. The key benefits include:

Features	Advantages and Potential Benefits
Outstanding load carrying, anti-wear, and extreme pressure performance	Helps to promote long transmission life.
Excellent prevention of deposits and lacquer formation	Helps to promote long seal life, extended drain, and service intervals
Excellent protection from corrosion of copper and its alloys	Helps to promote long life of synchronisers and smoother shifting performance
Effective thermal and oxidation resistance at high operating temperatures	Helps to promote reduced wear and long component life
Excellent shear stability	Maintains effective viscosity and film strength during severe operation
Good low-temperature fluidity	Easier, smoother shifting and quicker starts

Applications

- Recommended by ExxonMobil for use in:
- Cars, on highway light and heavy duty trucks, busses, and vans
  - Heavy duty automotive type drivetrains where API GL-4/GL-5 level performance is required

Specifications and Approvals

This product has the following approvals:
Mack GO-J
MAN 341 Typ Z2
MAN 342 Typ M2
ZF TE-ML 02B
ZF TE-ML 05A
ZF TE-ML 12L

<b>This product has the following approvals:</b>
ZF TE-ML 12M
ZF TE-ML 16B
ZF TE-ML 19B
ZF TE-ML 21A

<b>This product is recommended for use in applications requiring:</b>
API GL-4
MAN 341 Typ E2
Meritor O76-D
MIL (US) MIL-PRF-2105E
ZF TE-ML 08

<b>This product meets or exceeds the requirements of:</b>
API GL-5
API MT-1
R. Bosch AS TE-ML 08
ISUZU Axle Oil
Scania STO 1:0
ISUZU Large Manual Transmission Oil
ZF TE-ML 07A
SCANIA STO 1:1G

Properties and Specifications

Property	
Grade	SAE 80W-90
Density @ 15 C, g/cm3, ASTM D4052	0.9
Flash Point, Cleveland Open Cup, °C, ASTM D92	210
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	15
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	144
Pour Point, °C, ASTM D97	-30
Viscosity Index, ASTM D2270	105

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2023

ExxonMobil Lubricants and Specialties Europe division of ExxonMobil Petroleum & Chemical b.v.b.a.

Polderdijkweg

B-2030 Antwerpen, Belgium

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved