



### Mobil Super 3000 Formula M 5W-30

Mobil Passenger Vehicle Lube , Portugal

#### High performance motor oil

### Product Description

Mobil Super 3000 Formula M 5W-30 is a high performance motor oil primarily intended for use in Mercedes Benz (MB) vehicles where a product for extended service intervals (Long Life) service intervals is required.

### Features and Benefits

Mobil Super 3000 Formula M 5W-30 provides the following features and benefits:

- Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown.
- Provides excellent fluidity at low temperatures allowing easy winter starting and rapid oil circulation around the engine.
- Suitable for use in both gasoline and some diesel engine passenger car and light commercial vehicles.

### Applications

Mobil Super 3000 Formula M 5W-30 has been developed to meet the highest specifications for motor oils required by Mercedes Benz. It offers excellent performance at both very low and very high operating temperatures and long term engine protection from wear and sludge.

### Specifications and Approvals

|  |  |
|--|--|
| <b>Mobil Super 3000 Formula M 5W-30 has the following builder approvals:</b> |  |
| Mercedes Benz  | MB-Approval 229.5<br>MB-Approval 229.3 |

### Typical Properties

|   |      |
|---|------|
| <b>Mobil Super 3000 Formula M 5W-30</b> |      |
| Viscosity, ASTM D 445                   |      |
| cSt @ 40° C                             | 72.4 |
| cSt @ 100° C                            | 12.2 |
| Sulphated Ash, wt%, ASTM D 874          | 0.8  |
| Phosphorous                             | 0.08 |
| Flash Point, °C, ASTM D 92              | 212  |
| Density @15° C kg/l, ASTM D 4052        | 0.85 |
| Pour Point, °C, ASTM D 97               | -42  |

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobil Super are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

05-2020

ExxonMobil Lubricants and Specialties Europe division of ExxonMobil Petroleum & Chemical b.v.b.a.

Polderdijkweg

B-2030 Antwerpen, Belgium

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil Esso XTO

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved