



Mobil™ Gas Compressor Oil

Mobil Industrial , Paraguay

Gas Compressor Oil

Product Description

Mobil Gas Compressor Oil is a premium quality, high performance, synthetic gas compressor lubricant based on poly-alkylene glycol. It is primarily intended for use in gas compressors for hydrocarbon and chemical gases where the crankcases and bearings operate in a gas filled atmosphere. It is particularly suitable for marine service on vessels carrying liquefied gas cargoes. It also has application in general industry where problems with oil and gas solubility issues have resulted in less than satisfactory equipment performance. Compared with conventional mineral oil, Mobil Gas Compressor Oil has a lower gas solubility and consequently resists dilution and has improved viscosity control which results in additional protection against wear, improved efficiency and reduced foaming.

Features and Benefits

Mobil Gas Compressor Oil is a speciality synthetic product developed to reduce the problems resulting from gas dissolving in the lubricant and causing problems with wear, sealing, increased maintenance and frequent oil changes.

Features	Advantages and Potential Benefits
Reduced Hydrocarbon and Chemical Gas Solubility	Improved viscosity control Reduced component wear Reduced downtime and lower maintenance costs

Applications

- Liquefied petroleum gases such as propane and butane
- Liquefied natural gases such as methane and ethane
- Hydrocarbon chemical gases such as ethylene, propylene and butylene
- Chemical gases such as ammonia, vinyl chloride monomer and butadiene

Properties and Specifications

Property	
ASTM Color, ASTM D1544	<2.0
Flash Point, Cleveland Open Cup, °C, ASTM D92	294
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	175
Pour Point, °C, ASTM D97	-36
Density @ 15 C, kg/l, ASTM D1298	1.055

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2020

Autopiezas Esso Lubricantes (Distribuidor Oficial)

Avenida Madame Lynch c/ Aviadores del Chaco , Asuncion , Paraguay

(595 21) 674 900

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved