



Mobil Delvac Legend™ CH-4 15W-40 Heavy Duty

Mobil Commercial Vehicle Lube , Singapore

High Performance Diesel Engine Oil

Product Description

Mobil Delvac Legend™ CH-4 15W-40 Heavy Duty is a high performance diesel engine oil that provides protection of diesel engines operating on and off-hi applications. Mobil Delvac Legend™ CH-4 15W-40 Heavy Duty is biodiesel compatible\* and is recommended by ExxonMobil for use in a wide range of heav applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

This product is fully compatible with Mobil Delvac Super 1400 15w-40 and can be used as a replacement of same.

\*based on CEC L-109-14 (test modified with palm B100), meeting the limits in ACEA E7-16.

Features and Benefits

The technology in Mobil Delvac Legend CH-4 15W-40 Heavy Duty delivers excellent performance in both modern diesel engines as well as older models. Ti benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
TBN reserve	Deposit control
Stay-in-grade shear stability	Reduced oil consumption and wear protection
Excellent detergency/dispersancy	Clean engines and long engine life
Component compatibility	Long gasket and seal life

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture

Specifications and Approvals

This product has the following approvals:
MB-Approval 228.3
MTU Oil Category 2

This product is recommended for use in applications requiring:
API CF-4

**This product is recommended for use in applications requiring:**

API CF

API CG-4

Mack EO-M

VOLVO VDS-2

**This product meets or exceeds the requirements of:**

API CH-4

Cummins CES 20076

**Properties and Specifications**

Property	
Grade	SAE 15W-40
Ash, Sulfated, mass%, ASTM D874	1.2
Density @ 15 C, kg/l, ASTM D4052	0.869
Flash Point, Cleveland Open Cup, °C, ASTM D92	230
Viscosity Index, ASTM D2270	137
Total Base Number, mgKOH/g, ASTM D2896	8.2
Pour Point, °C, ASTM D97	-33
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	116
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	15.2

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2024

ExxonMobil Asia Pacific Ltd

1 HarbourFront Place

#06-00 HarbourFront Tower One

Singapore 098633

+65 6885 8000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

