



## Mobil Delvac™ MX City Logistics 10W-30

Mobil Commercial Vehicle Lube , Singapore

High Performance Diesel Engine Oil

### Product Description

Mobil Delvac™ MX City Logistics 10W-30 is formulated to deliver high performance in medium and light duty diesel engines and is suitable for use in the severe driving conditions typically encountered in city logistics operations. Mobil Delvac MX City Logistics 10W-30 provides protection on diesel engines under the conditions of frequent start-ups, stop and go driving in urban areas, and powerful driving for heavy loaded light commercial vehicles.

### Features and Benefits

Mobil Delvac™ MX City Logistics 10W-30 is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in modern diesel engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
High thermal and oxidation stability	Reduced sludge build-up, deposits and viscosity increase
TBN reserves	Deposit control and acid neutralisation
Stay-in-grade shear stability	Wear protection and viscosity control
Advanced detergency/dispersancy	Clean engines and long component life
Improved soot handling	Improved viscosity control and used oil pumpability
Excellent low temperature properties	Start-up wear protection
Component compatibility	Long gasket and seal life

### Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment from leading Japanese, European, and American manufacturers
- On-highway medium and light duty trucking

### Specifications and Approvals

Mobil Delvac™ MX City Logistics 10W-30 meets or exceeds the requirements of :
API CI-4

### Typical Properties

Mobil Delvac™ MX City Logistics 10W-30	
Viscosity, ASTM D 445	
cSt @ 40°C	81.1
cSt @ 100°C	11.7
Viscosity Index, ASTM D 2270	139
Sulfated Ash, wt%, ASTM D 874	1.0

Mobil Delvac™ MX City Logistics 10W-30	
Total Base # , mg KOH/g, ASTM D 2896	9
Pour Point, °C, ASTM D 97	-33
Flash Point, °C, ASTM D 92	228
Density @ 15°C kg/l, ASTM D 4052	0.870

## Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2022

ExxonMobil Asia Pacific Ltd

1 HarbourFront Place

#06-00 HarbourFront Tower One

Singapore 098633


+65 6885 8000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved