



## Mobil Super Moto™ 10W30 15W40 20W40 20W50

Mobil Passenger Vehicle Lube , Singapore

High Performance Four-Stroke Motorcycle Engine Oil

### Product Description

Mobil Super Moto™ 10W-30, 15W-40, 20W-40 and 20W-50 are high performance conventional four-stroke motorcycle engine oils primarily intended for general use in all types of four-stroke motorcycles and engines.

### Features and Benefits

Mobil Super Moto 10W-30, 15W-40, 20W-40 and 20W-50 combine highly refined, quality mineral oils and an advanced additive system to provide good engine cleanliness, good wear protection and corrosion protection. Motorcycle engine oils protect engine and gear and make clutch working.

### Key features and benefits include:

Features	Advantages and Potential Benefits
Good wear protection	Helps extend engine life
Thermal and oxidation stability	Helps keep engines clean for smoother operation
Good corrosion protection	Protects critical engine components
Broad viscosity range	Year round engine protection and performance

### Specifications and Approvals

Mobil Super Moto meets or exceeds the requirements of:	10W-30	15W-40	20W-40	20W-50
API	SL	SL	SL	SL
JASO	MA2	MA2	MA2	MA2

### Typical Properties

Mobil Super Moto	10W-30	15W-40	20W-40	20W-50
SAE Grade	10W-30	15W-40	20W-40	20W-50
Viscosity, ASTM D445				
cSt @ 40°C	71	99	122	185
cSt @ 100°C	10.5	13.7	15	20.5
Sulfated Ash, wt%, ASTM D874	0.8	0.8	0.8	0.8
Pour Point, °C, ASTM D97	-25	-30	-30	-33

Mobil Super Moto	10W-30	15W-40	20W-40	20W-50
Flash Point, °C, ASTM D92	220	230	230	230
Density @15°C g/ml, ASTM D4052	0.88	0.88	0.88	0.88

## Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2021

ExxonMobil Asia Pacific Ltd  
1 HarbourFront Place  
#06-00 HarbourFront Tower One  
Singapore 098633

+65 6885 8000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved