



## Mobil ATF SHC™

Mobil Passenger Vehicle Lube , Slovenia

Superior Performance Synthetic Automatic Transmission Fluid

### Product Description

Mobil ATF SHC™ is a superior performance synthetic automatic transmission fluid designed to meet the demanding requirements of automatic transmissions operating in the severe, high-temperature, and heavy load applications. The inherently high viscosity index and stability of Mobil ATF SHC protects against thermal breakdown at high operating temperatures enabling outstanding low temperature performance at ambient temperatures below "40°C.

### Features and Benefits

Mobil ATF SHC combines high performance synthesised hydrocarbon base oils with a balanced additive system to provide a significantly higher level of performance versus conventional fluids. This automatic transmission fluid ensures long fluid life, improved transmission cleanliness, excellent shift performance and extended transmission life under all operating conditions and performance levels. Key features and benefits include:

| Features   | Advantages and Potential Benefits  |
|--|--|
| Enhanced, long-term frictional properties                        | Improves and extends transmission efficiency, smooth shifting performance and potentially fuel savings |
| Outstanding thermal and oxidation stability                      | Keeps transmissions clean to extend life and performance even under severe operating conditions        |
| Outstanding film-strength and anti-wear properties               | Significant wear reduction and longer transmission life  |
| Excellent low-temperature fluidity                               | Provides prompt and reliable lubrication at ambient temperatures below "40° C                          |
| Exceptional shear stability                                      | Viscosity retention even under the severest heavy duty, high temperature operating conditions          |
| Compatible with mineral ATF fluids and all common seal materials | Reduced concern in top-off emergencies and excellent leakage control                                   |

### Applications

Mobil ATF SHC is recommended by ExxonMobil for use in modern high performance transmissions operating in the severe, high-temperature, heavy load or cold climate applications. It is ideal for manual transmissions designed to operate with ATF fluids, where it will provide excellent gear shifting and protection under severe operating conditions.

### Specifications and Approvals

| According to ExxonMobil, this product is of the following quality level: |
|--|
| Allison C-4  |
| CATERPILLAR TO-2   |
| GM DEXRON IIE  |

**According to ExxonMobil, this product is of the following quality level:**

Renk Doromat

**This product has the following builder approvals:**

MAN 339 Typ V2

MAN 339 Typ Z2

MB-Approval 236.8

R. Bosch AS Lubricant Class TE-ML 09X

### Properties and Specifications

| Property   |       |
|--|-------|
| Appearance, Visual   | Red   |
| Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983            | 7000  |
| Density @ 15 C, kg/l, ASTM D4052                           | 0.839 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92              | 210   |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 7.4   |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 33    |
| Pour Point, °C, ASTM D97                                   | -51   |
| Viscosity Index, ASTM D2270                                | 200   |

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved