



Mobil Super™ 1000 X1 15W-40

Mobil Passenger Vehicle Lube , Senegal

Premium Multigrade Passenger Vehicle Motor Oil

Product Description

Mobil Super™ 1000 x1 15W-40 is a premium conventional motor oil that provides long engine life.

Features and Benefits

Mobil Super 1000 products are industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super 1000 x1 15W-40 provides:

- Excellent engine cleanliness
- Good high temperature protection
- Good wear protection

Applications

Mobil Super 1000 products have been formulated to be suitable for use in nearly all vehicles. ExxonMobil recommends Mobil Super 1000 x1 15W-40 for daily use under normal conditions:

- Older engine technologies
- Gasoline and Diesel without Diesel Particulate Filters (DPF)
- Passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal operating conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
VW 501 01
VW 505 00
This product is recommended for use in applications requiring:
API CF
MB 229.1
This product meets or exceeds the requirements of:
ACEA A3/B3
API SJ

This product meets or exceeds the requirements of:
API SL
API SM
API SN
API SN PLUS

Properties and Specifications

Property	
Grade	SAE 15W-40
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	104
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14.5
Viscosity Index, ASTM D2270	143
Phosphorus, mass%, ASTM D4951	0.1
Ash, Sulfated, mass%, ASTM D874	0.9
Flash Point, Cleveland Open Cup, °C, ASTM D92	239
Pour Point, °C, ASTM D97	-39
Density @ 15.6 C, g/ml, ASTM D4052	0.87

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024
MOBIL OIL SENEGAL
KM 7,5 Boulevard du Centenaire de la Commune de Dakar, PO Box 227
Dakar, Senegal

+ 221 859 30 00

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved