



Nuto™ H Series

Mobil Industrial , Thailand

Hydraulic Oils

Product Description

Nuto™ H Series oils are good quality anti-wear hydraulic oils intended for industrial and mobile service applications, subjected to moderate operating conditions requiring anti-wear lubricants.

Their effective oxidation resistance and chemical stability support good oil life in moderate to severe applications.

Features and Benefits

- Good anti-wear performance helps reduce pump wear and prolonging pump life
- Corrosion protection helps reduce the effects of moisture on system components
- Filterability to prevent filter blockage even in the presence of water

Applications

- Systems using gear, vane, radial and axial piston pumps and those containing gears and bearings where mild anti-wear characteristics are required
- Where hydraulic oil contamination or leakage is unavoidable
- Where small amounts of water are unavoidable

Specifications and Approvals

| This product has the following approvals: | 32 | 46 | 68 | 100 | 150 |
|-------------------------------------------|----|----|----|-----|-----|
| DENISON HF-0                              | X  | X  | X  |     |     |

| This product meets or exceeds the requirements of: | 32 | 46 | 68 | 100 | 150 |
|----------------------------------------------------|----|----|----|-----|-----|
| DIN 51524-2:2017-06                                | X  | X  | X  | X   |     |
| ISO L-HM (ISO 11158:2023)                          | X  | X  | X  | X   | X   |

Properties and Specifications

| Property                                               | 32     | 46     | 68     | 100     | 150     |
|--------------------------------------------------------|--------|--------|--------|---------|---------|
| Grade                                                  | ISO 32 | ISO 46 | ISO 68 | ISO 100 | ISO 150 |
| Copper Strip Corrosion, 3 h, 100 C, Rating, ASTM D130  | 1A     | 1A     | 1A     | 1A      | 1A      |
| Density @ 15 C, kg/l, ASTM D1298                       | 0.872  | 0.876  | 0.882  | 0.884   | 0.887   |
| Emulsion, Time to 3 mL Emulsion, 54 C, min, ASTM D1401 | 15     | 15     | 20     |         |         |
| Emulsion, Time to 3 mL Emulsion, 82 C, min, ASTM D1401 |        |        |        | 10      | 5       |
| Flash Point, Cleveland Open Cup, °C, ASTM D92          | 212    | 226    | 234    | 242     | 258     |

| Property                                      | 32   | 46   | 68   | 100  | 150  |
|-----------------------------------------------|------|------|------|------|------|
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 5.3  | 6.6  | 8.3  | 11.0 | 14.9 |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445  | 31.4 | 44.0 | 63.3 | 96.0 | 150  |
| Pour Point, °C, ASTM D97                      | -24  | -24  | -18  | -18  | -18  |
| Viscosity Index, ASTM D2270                   | 98   | 98   | 98   | 98   | 98   |

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024  
ExxonMobil Marketing (Thailand) Limited  
3195/26, 22nd Floor, Rama IV Road  
Klong Ton, Klong Toey District  
Bangkok 10110  
Thailand

+66 2 407 4000  
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)  
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

NUTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved