



## MOBIL SUPER FRICTION FIGHTER DIESEL 15W40

Mobil Passenger Vehicle Lube , Thailand

Mobil passenger-vehicle-lube High Performance Synthetic Technology Diesel Engine Oil

### Product Description

Mobil Super™ Friction Fighter Diesel Turbospeed 15W-40 is brought to you by the makers of Mobil 1™. This synthetic technology engine oil is specially engineered with enhanced engine wear protection to prolong your engine life.

It is formulated with Friction Fighter™ molecules to create a solid protective layer that cushions the impact when engine parts come in contact, protecting your engine against life-shortening wear.

### Features and Benefits

- Proprietary Friction Fighter™ molecules
- Outstanding wear protection for long engine life
- Excellent high temperature protection under severe operating conditions

### Applications

Mobil Super™ Friction Fighter Diesel Turbospeed 15W-40 is suitable for use in the diesel pickup trucks, SUVs, vans, and cars from leading Japanese, European, and American manufacturers.

Mobil Super™ Friction Fighter Diesel Turbospeed 15W-40 is also recommended for turbo-charged and common rail diesel engines.

Always consult your owner's manual to check the recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

This product meets or exceeds the requirements of:
API CI-4
API SL

### Properties and Specifications

Property	
Grade	SAE 15W-40
Density @ 15 C, kg/l, ASTM D4052	0.88
Viscosity Index, ASTM D2270	136
Total Base Number, mgKOH/g, ASTM D2896	9.2

Property	
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.6
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	110.2
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10 <sup>(6)</sup> sec <sup>(-1)</sup> , mPa.s, ASTM D4683	4.1
Mini-Rotary Viscometer, Apparent Viscosity, -25 C, mPa.s, ASTM D4684	15900
Ash, Sulfated, mass%, ASTM D874	1.1
Flash Point, Cleveland Open Cup, °C, ASTM D92	225
Pour Point, °C, ASTM D97	-36

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil Marketing (Thailand) Limited

3195/26, 22nd Floor, Rama IV Road

Klong Ton, Klong Toey District

Bangkok 10110

Thailand


+66 2 407 4000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved