



Mobil Delvac XHP™ ESP 10W-40

Mobil Commercial Vehicle Lube , Tunisia

Emission System Protection Diesel Engine Oil

Product Description

Mobil Delvac XHP ESP 10W-40 is a synthetic extra high performance diesel engine oil engineered to provide lubrication to modern, high performance, low emissions engines used in severe applications. This engine oil is designed using high performance base oils which provide excellent low temperature fluidity, high temperature viscosity retention and volatility control. The new advanced additive system has been expertly engineered to help towards long engine life(1) and maintain the efficiency of emission reduction systems including the Diesel Particulate Filter (DPF). Its specifications and approvals allow Mobil Delvac XHP ESP 10W-40 to target mixed fleet applications. Mobil Delvac XHP ESP 10W-40 is biodiesel compatible.(2)

(1) Well formulated oils, like Mobil Delvac, that meet or exceed industry or OEM specifications, can help protect engines. Consult OEM for optimum fluid selection. Actual results may vary depending on OEM requirements, type of engine and its maintenance, application and service conditions, and prior lubricant used. (2) Follow OEM recommendations on potential service adjustments

Features and Benefits

High output, low emission engines significantly increase demands on engine lubricants. Tighter engine design, use of inter-coolers, and turbochargers increase thermal stresses on the lubricant. Low emission engine technologies such as higher fuel injection pressure, retarded timing and aftertreatment devices all require improved oil performance in areas such as oxidation stability, soot dispersancy, volatility and compatibility with aftertreatment devices. The advanced technology in Mobil Delvac XHP ESP 10W-40 delivers exceptional performance, long drain interval capability and protection of exhaust systems including those fitted with Diesel Particulate Filters (DPF). The key benefits include:

¹ Well formulated oils, like Mobil Delvac, that meet or exceed industry or OEM specifications, can help protect engines. Consult OEM for optimum fluid selection. Actual results may vary depending on OEM requirements, type of engine and its maintenance, application and service conditions, and prior lubricant used.

| Features | Advantages and Potential Benefits |
|--|---|
| Outstanding protection against oil thickening, high temperature deposits, sludge build-up and, oil degradation | Provides capability for long drain intervals Helps to protect against ring sticking |
| Excellent anti-wear, anti-scuff properties and bore polishing and corrosion protection. | Helps to towards long engine life ¹ |
| Stay-in-grade shear stability. Very low volatility | Helps to reduce viscosity breakdown and oil consumption under heavy duty, high temperature operating conditions |
| Low ash, sulfur and phosphorous levels | Helps to protect exhaust systems devices like those fitted with DPF |
| Excellent low temperature properties | Helps to improve pumpability and oil circulation |

Applications

- Heavy Duty Diesel Engines including Euro V/VI Modern Low Emissions Vehicles, Utilizing Technologies such as Diesel Particulate Filter (DPF), Selective Catalytic Reduction (SCR), Continuously Regenerating Traps (CRT), Diesel Oxidation Catalysts (DOC) and Exhaust Gas Recirculation (EGR)
 - Heavy Duty Diesel Engines using low sulfur diesel fuels and many biodiesel fuel formulations
 - Naturally Aspirated and Turbo-Charged Diesel Powered Equipment
 - On-Highway Short-Haul and Long-Haul Trucks and Buses
 - Off-Highway Mining, Construction and Agricultural Equipment

(2) Please refer to the owners handbook for OEM application requirements and oil drain intervals for your vehicle or equipment

Specifications and Approvals

| This product has the following approvals: |
|--|
| MAN M 3775 |
| MACK EOS-4.5 |
| Mack EO-O Premium Plus |
| MB-Approval 228.51 |
| RENAULT TRUCKS RLD-2 |
| RENAULT TRUCKS RLD-3 |
| VOLVO VDS-3 |
| VOLVO VDS-4 |
| VOLVO VDS-4.5 |
| DQC IV-18 LA |

| This product is recommended for use in applications requiring: |
|---|
| MAN M 3271-1 |
| MAN M 3575 |
| IVECO 18-1804 TLS E9 |
| MANM 3477 |
| Scania Low Ash |

| This product meets or exceeds the requirements of: |
|---|
| ACEA E4 |
| ACEA E6 |
| ACEA E7 |
| ACEA E9 |
| API CI-4 |
| API CI-4 PLUS |
| API CH-4 |
| API CJ-4 |

This product meets or exceeds the requirements of:

API CK-4

Caterpillar ECF-3

Cummins CES 20081

Cummins CES 20086

DAF Extended Drain

ISUZU DEO (w/ DPD Equipped Vehicles)

JASO DH-2

Properties and Specifications

| Property | |
|--|-------|
| Density @ 15.6 C, kg/l, ASTM D4052 | 0.861 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 232 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 13.7 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 91 |
| Pour Point, °C, ASTM D97 | -30 |
| Viscosity Index, ASTM D2270 | 153 |
| Base Number, mgKOH/g, ASTM D2896 | 13.2 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2022

ExxonMobil Tunisie

Immeuble Ennouzha 2, Rue 8301

Cité Montplaisir, BP 237

1002 Tunis Belvédère, Tunisie

+ 216 71 951 510

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved