



Mobil Delvac CT 10W-30

Mobil Commercial Vehicle Lube , Turkey

Heavy Duty Diesel Engine Oil

Product Description

Mobil Delvac CT 10W-30 is a high performance diesel engine oil specifically engineered to provide excellent lubrication of diesel engines operating in severe applic

This diesel engine oil is designed using a blend of high performance base oils to provide excellent low temperature fluidity, high temperature viscosity retentio

volatility control. These base oils are enhanced with an advanced additive system, which provides a high level of protection to all parts of the engine.

Features and Benefits

The technology in Mobil Delvac CT 10W-30 delivers strong performance in both modern diesel engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
Good protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion	Helps to control of high temperature deposits Helps to reduce wear and to provide long engine life Protection against ring sticking
Excellent low temperature properties	Ready oil "pumpability" / circulation Start-up wear protection
Stay-in-grade shear stability	Viscosity maintenance and reduced oil consumption under heavy-duty, high erature operating conditions

Applications

- Recommended by ExxonMobil for use in:
- Recommended for use in turbo-charged, low emission diesel engines of European and American design
 - On highway applications operating in both high speed/high load and short haul pick-up/delivery in light and heavy-duty trucking
 - Off highway applications operating in heavy load conditions in construction, mining, quarrying and agriculture

Specifications and Approvals

Mobil Delvac CT 10W-30 meets or exceeds the requirements of:	
API CH-4	X

Mobil Delvac CT 10W-30 is recommended by ExxonMobil for use in applications requiring
API CG-4/CF-4/CF

Typical Properties

Mobil Delvac CT 10W-30	
SAE Grade	10W-30
Viscosity, ASTM D 445	
cSt @ 40°C	70
cSt @ 100°C	10.7
Viscosity Index, ASTM D 2270	138
Sulfated Ash, wt%, ASTM D 874	1.2

Mobil Delvac CT 10W-30	
Total Base, mg KOH/g, ASTM D 2896	9.9
Pour Point, °C, ASTM D 97	-27
Flash Point, °C, ASTM D 92	206
Density @ 15°C kg/l, ASTM D 4052	0.88

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Delvac CT are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

Mobil Oil Türk A.S.

Pakpen Plaza Halk Sokak No: 40-44 34734 Kozyatagi Istanbul

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobiloil.com.tr/tr-tr/contact-us>

Tel: +90 850 390 4939

<http://www.mobiloil.com.tr>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTREME

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved