



## Mobil Delvac Modern™ Light Commercial 10W-40

Mobil Commercial Vehicle Lube , Turkey

Multigrade Light Duty Diesel Engine Oil

### Product Description

Mobil Delvac Modern™ Light Commercial 10W-40 is Multigrade light duty commercial engine oil that provides excellent lubrication of diesel and gasoline engines operating in severe driving conditions typically encountered in city operations. This product is recommended by ExxonMobil for European, Russian and American engines for use in a wide range of traditional light-duty commercial vehicles.

Mobil Delvac Modern Light Commercial 10W-40 is engineered with a blend of advanced synthetic technology base stocks and additive system to provide a strong foundation for oxidation resistance, soot handling, and wear control supplemented with excellent piston deposit protection and reduced sludge formation to help provide long engine life.

### Features and Benefits

Mobil Delvac Modern Light Commercial 10W-40 is formulated to provide optimum engine performance in modern diesel and gasoline engine

Features	Advantages and Potential Benefits
Increased thermal and oxidation stability	Help to reduced sludge build-up, deposits, and long oil and engine life
Enhanced wear protection	Helps towards long component and engine life
Improved corrosion protection	Helps to reduce bearing wear to assist with long drain intervals in modern diesel engines
Advanced piston deposit control	Helps to keep engines clean with reduced maintenance costs and long engine life
Advanced soot handling to control viscosity increase, sludge build up, and filter pressure	Helps to enhance engine protection for long engine life
Enhanced low temperature pumpability	Fast start up with reduced wear operating in low temperature climates

### Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered engines built by European, Russian, and American manufacturers
- On-highway light trucking including mixed fleets with gasoline engines.
- For GAZ Light Duty Vehicles with diesel or petrol engines requiring API CI-4 or API SL motor oils

### Specifications and Approvals

This product has the following approvals:

**This product has the following approvals:**

MB-Approval 228.3

Cummins CES 20077

Cummins CES 20078

**This product is recommended for use in applications requiring:**

ACEA A2

ACEA B2

API CF

API CF-4

API CG-4

Cummins CES 20071

Cummins CES 20072

**This product meets or exceeds the requirements of:**

API CI-4

API CH-4

API SJ

API SL

ACEA E7

Cummins CES 20076

**Properties and Specifications**

Property	
Grade	SAE 10W-40
Density @ 15 C, g/ml, ASTM D1298	0.867
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.8
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	100
Pour Point, °C, ASTM D97	-36
Ash, Sulfated, mass%, ASTM D874	1.2

Property	
Flash Point, Cleveland Open Cup, °C, ASTM D92	210
Total Base Number, mgKOH/g, ASTM D2896	11.1
Viscosity Index, ASTM D2270	154

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2024

Mobil Oil Türk A.S.

Pakpen Plaza Halk Sokak No: 40-44 34734 Kozyatagi Istanbul

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobiloil.com.tr/tr-tr/contact-us>

Tel: +90 850 390 4939

<http://www.mobiloil.com.tr>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved