



## Mobil Delvac™ Light Commercial Vehicle F 0W-30

Mobil Commercial Vehicle Lube , Turkey

Synthetic Light Commercial Vehicle Engine Oil

### Product Description

Mobil Delvac™ Light Commercial Vehicle F 0W-30 is a fully synthetic engine oil developed to meet the Ford requirement "WSS-M2C950-A". It is designed to help provide long engine life and outstanding protection for diesel engines operating in severe driving conditions, typically encountered in city operations.

This product is designed for Ford light-duty commercial vehicles but ExxonMobil also recommends it for vans which need to meet requirements of ACEA A5/B5 and ACEA C2.

### Features and Benefits

Mobil Delvac Light Commercial Vehicle F 0W-30 meets the technical requirements according to Ford's standard WSS-M2C950-A, based on the OEM engine tests.

The usage of this product is meant to provide the following benefits:

- Increased fuel economy 1
- Extended life of diesel particulate filter 2
- Enhanced lower temperature properties 3
  1. based on 950-A 0W-30 spec compared to the 913-D 5W-30 oil
  2. based on ACEA C2 requirements
  3. based on 0W-30 spec compared to 5W-30 oil

### Applications

ExxonMobil recommends Mobil Delvac™ Light Commercial Vehicle F 0W-30 for demanding driving conditions:

- Ford Light Commercial Vehicles for engines requiring WSS-M2C950-A
- Light Commercial Vehicles requiring ACEA A5/B5 and ACEA C2
- Normal to occasionally severe operating conditions (including city driving conditions)

Owner's manual should be consulted for recommended viscosity grades and specification.

### Specifications and Approvals

This product meets or exceeds the requirements of:
ACEA A5/B5
ACEA C2-16
FORD WSS-M2C950-A

### Properties and Specifications

Property	
Grade	SAE 0W-30
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	45
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	9.6
Density @ 15.6 C, g/ml, ASTM D4052	0.84
Total Base Number, mgKOH/g, ASTM D2896	8
Cold-Cranking Simulator, Apparent Viscosity @ -35 C, mPa.s, ASTM D5293	5100
Noack Volatility, mass%, ASTM D5800	12
Ash, Sulfated, mass%, ASTM D874	0.77
Viscosity Index, ASTM D2270	204
Flash Point, Cleveland Open Cup, °C, ASTM D92	232
Pour Point, °C, ASTM D97	-42

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2021

Mobil Oil Türk A.S.

Pakpen Plaza Halk Sokak No: 40-44 34734 Kozyatagi Istanbul

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobiloil.com.tr/tr-tr/contact-us>

Tel: +90 850 390 4939

<http://www.mobiloil.com.tr>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved