



Mobil Delvac Modern™ Light Commercial T 5W-30

Mobil Commercial Vehicle Lube , Turkey

High performance light Duty engine Oil

Product Description

Mobil Delvac Modern™ Light Commercial T 5W-30 is a high performance synthetic technology engine oil that provides long engine life and protection against sludge and wear.in diesel and gasoline engines.

Features and Benefits

Mobil Delvac Modern™ Light Commercial T 5W-30 is industry proven so you can trust you will get the performance you want from your vehicle. Mobil Delvac Modern™ Light Commercial T 5W-30 provides:

- Excellent sludge prevention
- Excellent engine cleanliness
- Excellent high temperature protection
- Excellent wear protection
- Good cold start-up performance

Applications

ExxonMobil recommends Mobil Delvac Modern™ Light Commercial T 5W-30 for:

- Older engine technologies
- Gasoline and Diesel without Diesel Particulate Filters (DPF)
- Light trucks and vans
- Highway cruising and stop and go city driving
- Normal to occasionally severe operating conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Standard oil drain up to 15.000km/1 year

Specifications and Approvals

| |
|--|
| This product has the following approvals: |
| VW 502 00 |
| VW 505 00 |

| |
|---|
| This product is recommended for use in applications requiring: |
| API CF |

This product is recommended for use in applications requiring:

MB 229.3

This product meets or exceeds the requirements of:

API SJ

API SL

ACEA A3/B4

Properties and Specifications

| Property | |
|--|-----------|
| Grade | SAE 5W-30 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 12.2 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 74 |
| Pour Point, °C, ASTM D97 | -39 |
| Ash, Sulfated, mass%, ASTM D874 | 1.2 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 235 |
| Viscosity Index, ASTM D2270 | 163 |
| Total Base Number, mgKOH/g, ASTM D2896 | 11 |
| Cold-Cranking Simulator, Apparent Viscosity @ -30 C, mPa.s, ASTM D5293 | 6000 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2024

Mobil Oil Türk A.S.

Pakpen Plaza Halk Sokak No: 40-44 34734 Kozyatagi Istanbul

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobiloil.com.tr/tr-tr/contact-us>

Tel: +90 850 390 4939

<http://www.mobiloil.com.tr>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved