



Mobil Super™ Synthetic Formula B 5W-40

Mobil Passenger Vehicle Lube , Turkey

Synthetic Passenger Vehicle Engine Oil

Product Description

Mobil Super™ Synthetic Formula B 5W-40 is a full synthetic high-performance motor oil, which provides excellent high temperature protection even under operating conditions. Mobil Super Synthetic Formula B 5W-40 is designed to help provide long engine life and outstanding protection in vehicles of all outperforming our conventional-synthetic blended products. It provides outstanding protection against sludge, engine rust and corrosion under sever low-temperature operating conditions, and provides optimum viscosity and fluidity across a broad range of temperatures.

Features and Benefits

Mobil Super Synthetic Formula B 5W-40 presents the following features and benefits:

- Helps extend engine life
- Outstanding wear protection for vehicles of all ages
- Excellent high temperature protection to help keep engines cool
- Helps control oil consumption and loss
- Allows easy starting and rapid oil circulation during cold starts to protect critical engine parts
- Specifically formulated to support European designed engines

Applications

Mobil Super Synthetic Formula B 5W-40 is recommended for gasoline and diesel vehicles without exhaust gas after treatment systems. Before using Mobil S Synthetic Formula B 5W-40 engine oils, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade.

Specifications and Approvals

|  |
|--|
| This product has the following approvals:                      |
| PSA B712296  |
| This product is recommended for use in applications requiring: |
| API CF   |
| This product meets or exceeds the requirements of:             |
| ACEA A3/B3   |
| ACEA A3/B4   |
| API SJ   |
| API SL   |
| API SN   |
| API SM   |

Properties and Specifications

| Property                                      |           |
|---|-----------|
| Grade   | SAE 5W-40 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 13        |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445  | 69.5      |
| Density @ 15 C, g/ml, ASTM D4052              | 0.85      |
| Pour Point, °C, ASTM D97                      | -39       |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 238       |
| Ash, Sulfated, mass%, ASTM D874               | 1.1       |
| Phosphorus, mass%, ASTM D4951                 | 0.10      |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2024  
Mobil Oil Türk A.S.  
Pakpen Plaza Halk Sokak No: 40-44 34734 Kozyatagi Istanbul

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobiloil.com.tr/tr-tr/contact-us>

Tel: +90 850 390 4939  
<http://www.mobiloil.com.tr>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)  
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTOMobil

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved