



## Mobil Delvac Legend™ 1330

Mobil Commercial Vehicle Lube , Taiwan

Heavy Duty Diesel Engine Oils

### Product Description

Mobil Delvac Legend™ 1330 is a high performance, heavy duty diesel engine oil formulated from advanced technology base oils and a balanced additive system. They are specifically engineered for performance in intercooled, turbo-charged engines operating under severe on and off highway conditions. Mobil Delvac Legend 1300 monogrades are used in a wide range of applications where a monograde lubricant is recommended.

### Features and Benefits

| Features   | Advantages and Potential Benefits  |
|--|--|
| Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion | Prolonged engine life<br>Less wear<br>Excellent protection against ring sticking |
| Extended TBN reserve   | Long-term deposit/wear control   |

### Applications

- \* Naturally aspirated and turbo-charged diesel powered equipment
- \* On highway light and heavy duty trucking
- \* Off highway industries including: construction, mining, quarrying, and agriculture.

### Specifications and Approvals

|   |
|---|
| <b>This product is recommended for use in applications requiring:</b> |
| API CF  |

### Properties and Specifications

| Property                               |        |
|--|--------|
| Grade                                  | SAE 30 |
| Pour Point, °C, ASTM D97               | 33     |
| Total Base Number, mgKOH/g, ASTM D2896 | 6.7    |
| Viscosity Index, ASTM D2270            | 104    |
| Ash, Sulfated, mass%, ASTM D874        | 0.7    |

| Property   |       |
|--|-------|
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 11.2  |
| Flash Point, Cleveland Open Cup, °C, ASTM D92              | 240   |
| Density @ 15 C, g/ml, ASTM D1298                           | 0.886 |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 93.4  |

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2023

ExxonMobil international Holding Inc. Taiwan Branch  
6F, No 2, Section 1, Tun Hua South Road  
Taipei Taiwan

+886 2 2734 6888

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved