



Mobil Brake Fluid DOT 3

Mobil Passenger Vehicle Lube , Taiwan

High Performance Hydraulic Brake Fluid

Product Description

Mobil Brake Fluid DOT 3 is a high performance hydraulic brake fluid for use in automotive disc, drum and anti-skid brake systems and clutch systems.

Features and Benefits

Mobil Brake Fluid DOT 3 is based on polyethylene glycol ether technology to provide a high level of brake and clutch performance in automotive and commercial ve

Key features and benefits include:

Features	Advantages and Potential Benefits
High boiling point	Consistent and safe brake performance under high braking pressure
Minimum rubber component swell	Reduces leakage and loss of fluid to a minimum
Excellent corrosion protection	Improved life and reliability of brake system components

Applications

Mobil Brake Fluid DOT 3 is recommended by ExxonMobil for use in applications where disc, drum and anti-skid braking systems are used in vehicles requiring DOT performance.. ExxonMobil recommendations for use include:

- Use only in its concentrated form out of a previously unopened or well sealed container
- Always seal the container immediately after use as the fluid absorbs moisture from the atmosphere quite rapidly; this will reduce service life significantly.
- Never reuse drained brake fluid.
- Brake fluid can affect the vehicle paintwork, so remove spills immediately without rubbing.
- Brake fluid should be drained from the vehicle every two years or 40,000 Km (24,000 Miles) and refilled.
- Check Owners Operators Manual for details.

Specifications and Approvals

This product meets or exceeds the requirements of:
FMVSS 116 DOT 3
ISO 4925:2005 Class 3
SAE J1703

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

The Mobil logotype, the Pegasus design, and Brake Fluid DOT 3 are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

6F, No 2, Section 1, Tun Hua South Road
Taipei Taiwan

+886 2 2734 6888

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved