



Mobil™ ATF 220 Syn Tech

Mobil Passenger Vehicle Lube , Taiwan

Automatic Transmission Fluid

Product Description

Mobil™ ATF 220 Syn Tech is a high performance fluid for automatic transmissions in vehicles requiring Dexron II/IIID. It is also used as a hydraulic fluid in unique applications.

Features and Benefits

Mobil ATF 220 Syn Tech is formulated from high-quality conventional base oils combined with a special additive system including viscosity index improvers, antioxidants, and defoamers providing smooth and controlled friction/wear characteristics. The product provides consumers an excellent driving experience even in broad range of driving conditions in a wide variety of automobiles requiring Dexron II/IIID specifications.

Features	Advantages and Potential Benefits
Good thermal and oxidation stability	Resists lacquer, sludge and deposit formation to keeps transmissions clean for efficient operation over the fill life
Good anti-wear properties	Meets the wear requirement to promote longer transmission life
Excellent low-temperature fluidity	Assist in improved start-up and clean fast lubrication at low ambient temperatures
Effective foam control properties	Smooth and lasting shift feel and reduced fluid loss in severe service-operating conditions
Compatible with all common seal materials used in Type IID transmissions	Maintains effective leakage control

Applications

Mobil ATF 220 Syn Tech is recommended for some automatic and manual transmissions in passenger cars and light trucks specifying Dexron II/IIID level performance as well as the related power steering systems. It is also suitable for use in some special hydraulic systems in farm equipment and other installations having similar fluid requirements. It is recommended that the user consult the manufacturer's requirements. Other applications include:

- Off-highway transmissions power steering and other hydraulic systems.
- Industrial hydraulic systems and components.

This product is recommended for use in applications requiring:

Ford ESR-M2C163-A2

GM DEXRON II

GM DEXRON IID

GM Type A Suffix A

MB 236.7

R. Bosch AS TE-ML 09

Specifications and Approvals

This product is recommended for use in applications requiring:
Ford ESR-M2C163-A2
GM DEXRON II
GM DEXRON IID
GM Type A Suffix A
MB 236.7
R. Bosch AS TE-ML 09

Properties and Specifications

Property	
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	7
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	40.5
Flash Point, Cleveland Open Cup, °C, ASTM D92	229
Pour Point, °C, ASTM D97	-42
Color, Visual	Red
Density @ 15 C, g/cm ³ , ASTM D4052	0.8624
Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983	41200
Viscosity Index, ASTM D2270	131

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2023

ExxonMobil international Holding Inc. Taiwan Branch

6F, No 2, Section 1, Tun Hua South Road

Taipei Taiwan

+886 2 2734 6888

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local

ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved