



## Mobil 1™ 0W-20

Mobil Passenger Vehicle Lube , Taiwan

Advanced Full Synthetic Engine Oil

### Product Description

Mobil 1 0W-20 is an advanced full synthetic engine oil designed delivering great engine performance. Mobil 1 0W-20 is engineered for gasoline engine technology delivering excellent performance, including cleaning power, wear protection and fuel economy. Mobil 1 0W-20 keeps your engine running like new in all driving conditions.

### Features and Benefits

Excellent engine performance and wear protection

Enhanced frictional properties, excellent fuel economy

Quick cold weather starting for ultra fast protection

Keeps your engine clean

Protects engines working under high temperatures

provide excellent LSPI protection.

### Applications

Mobil 1 0W-20 is recommended for many types of modern vehicles where it will help provide the performance required even under very demanding driving conditions.

### Specifications and Approvals

#### This product has the following approvals:

GM Dexos1 Gen3

#### This product is recommended for use in applications requiring:

GM 6094M

FIAT 9.55535-CR1

#### This product meets or exceeds the requirements of:

API SJ

API SL

API SM

API SN

**This product meets or exceeds the requirements of:**

API SN PLUS

API SN PLUS RESOURCE CONSERVING

API SN Resource Conserving

API SP

API SP Resource Conserving

ILSAC GF-6A

ACEA C5

FORD WSS-M2C962-A1

CHRYSLER MS-6395

**Properties and Specifications**

Property	
Grade	SAE 0W-20
Pour Point, °C, ASTM D97	-48
Total Base Number, mgKOH/g, ASTM D2896	9.2
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	13600
Viscosity Index, ASTM D2270	163
Density @ 15.6 C, g/ml, ASTM D4052	0.845
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	8.4
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10 <sup>(6)</sup> sec <sup>(-1)</sup> , mPa.s, ASTM D4683	2.6
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	45
Flash Point, Cleveland Open Cup, °C, ASTM D92	235
Ash, Sulfated, mass%, ASTM D874	0.76

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2024

ExxonMobil international Holding Inc. Taiwan Branch

6F, No 2, Section 1, Tun Hua South Road

Taipei Taiwan

+886 2 2734 6888

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**

Exxon Mobil Esso XTO  
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All  
Rights Reserved