



## Mobil Super™ 1000 15W-50

Mobil Passenger Vehicle Lube , Taiwan

Premium Multigrade Passenger Vehicle Engine Oils

### Product Description

Mobil Super™ 1000 15W-50 is high quality premium multigrade™ motor oils designed to provide a high level of performance and protection under most operating conditions.

### Features and Benefits

Mobil Super 1000 15W-50 is meticulously engineered for today's tougher engine specifications. It provides very good engine protection and extends engine life.

- Excellent anti-wear protection
- Excellent engine cleanliness

### Applications

Mobil Super 1000 15W-50 is suitable for use in gasoline vehicles, and is ideally suited for less stressful driving conditions such as highway driving and lower consistent speed conditions.

### Specifications and Approvals

**This product meets or exceeds the requirements of:**

API SL

API SM

API SN

API SP

API SN PLUS

### Properties and Specifications

Property	
Grade	SAE 15W-50
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	17.2
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	132
Viscosity Index, ASTM D2270	142
Density @ 15.6 C, g/ml, ASTM D4052	0.874
Pour Point, °C, ASTM D97	-24

Property	
Flash Point, Cleveland Open Cup, °C, ASTM D92	230
Ash, Sulfated, mass%, ASTM D874	0.8
Total Base Number, mgKOH/g, ASTM D2896	7.5
Mini-Rotary Viscometer, Apparent Viscosity, -25 C, mPa.s, ASTM D4684	25800
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	4.5

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2020

ExxonMobil international Holding Inc. Taiwan Branch

6F, No 2, Section 1, Tun Hua South Road

Taipei Taiwan

+886 2 2734 6888

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**

Exxon

Mobil

Esso

XTO  
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved