



## Mobil Brake Fluid DOT 3

Mobil Passenger Vehicle Lube , Taiwan

High Performance Hydraulic Brake Fluid

### Product Description

Mobil Brake Fluid DOT 3 is a high performance hydraulic brake fluid for use in automotive disc, drum and anti-skid brake systems and clutch systems.

### Features and Benefits

Mobil Brake Fluid DOT 3 is based on polyethylene glycol ether technology to provide a high level of brake and clutch performance in automotive and commercial vehicles. Key features and benefits include:

Features	Advantages and Potential Benefits
High boiling point	Consistent and safe brake performance under high braking pressure
Minimum rubber component swell	Reduces leakage and loss of fluid to a minimum
Excellent corrosion protection	Improved life and reliability of brake system components

### Applications

Mobil Brake Fluid DOT 3 is recommended by ExxonMobil for use in applications where disc, drum and anti-skid braking systems are used in vehicles requiring DOT 3 level performance.. ExxonMobil recommendations for use include:

- Use only in its concentrated form out of a previously unopened or well sealed container
- Always seal the container immediately after use as the fluid absorbs moisture from the atmosphere quite rapidly; this will reduce service life significantly.
- Never reuse drained brake fluid.
- Brake fluid can affect the vehicle paintwork, so remove spills immediately without rubbing.
- Brake fluid should be drained from the vehicle every two years or 40,000 Km (24,000 Miles) and refilled.
- Check Owners Operators Manual for details.

### Specifications and Approvals

Mobil Brake Fluid DOT 3 meets or exceeds the requirements of the following industry specifications:	
FMVSS 116 DOT 3	
SAE J1703	
ISO 4925 Class 3	

### Health and Safety

Based on available information, avoid contact with the skin and eyes. Do not siphon with the mouth. Keep the Brake Fluid container tightly closed. If poisoning occurs, contact a doctor or Poisons Information Centre. If swallowed, and if more than 15 minutes from a hospital, induce vomiting, preferably using Ipecac Syrup APF. If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If in eyes, hold eyes open, flood with water for at least fifteen minutes and see a doctor. The Brake fluid container should not be used for any other purpose. This product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other

than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Brake Fluid DOT 3 are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

ExxonMobil international Holding Inc. Taiwan Branch

6F, No 2, Section 1, Tun Hua South Road

Taipei Taiwan

+886 2 2734 6888

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved